

REGISTRATION RECORD SERIES

International Alloy Designations and Chemical Composition Limits for Wrought Aluminum and Wrought Aluminum Alloys

Unified North American and International Registration Records

The Aluminum Association

900 19th Street, N.W., Washington, D.C. 20006

Revised:

July 1998

Supersedes:

February 1997 Blue Sheets December 1993 Green Sheets STD.AA SRCH REG 4-ENGL 1998 ■ 0604500 0014193 051 ■

Use of the Information

The Aluminum Association has used its best efforts in compiling the information contained in this publication. Although the Association believes that its compilation procedures are reliable, it does not warrant, either expressly or impliedly, the accuracy or completeness of this information. The Aluminum Association assumes no responsibility or liability for the use of the information herein.

All Aluminum Association published standards, data, specifications and other material are reviewed at least every five years and revised, reaffirmed or withdrawn. Users are advised to contact The Aluminum Association to ascertain whether the information in this publication has been superseded in the interim between publication and proposed use.

CONTENTS

Page
FOREWORD
SIGNATORIES TO THE DECLARATION OF ACCORD ii-ii
REGISTERED DESIGNATIONS AND CHEMICAL COMPOSITION LIMITS 1-9 Footnotes
TABLE OF NOMINAL DENSITIES FOR ACTIVE ALLOYS 11-14
TABLE OF INACTIVE ALLOY DESIGNATIONS
CROSS REFERENCES OF INTERNATIONAL DESIGNATIONS— DECLARATION OF ACCORD (DOA) TO ISO
RECOMMENDATION TO THE DECLARATION OF ACCORD
DECLARATION OF ACCORD

FOREWORD

Listed herein are designations and chemical composition limits for wrought aluminum and wrought aluminum alloys registered with The Aluminum Association. Numerical designations are assigned in accordance with the *Recommendation—International Designation System for Wrought Aluminum and Wrought Aluminum Alloys*, which is printed on pages 18 through 20. Additions may be made in accordance with the rules outlined in the Declaration of Accord printed on page 21, and alloys will be deleted when no longer in commercial use (see table of inactive alloys).

This edition of the International Alloy Designations and Chemical Composition Limits for Wrought Aluminum and Wrought Aluminum Alloys combines the North American (Green Sheets) and the International (Blue Sheets) registration records into one publication and includes significant additions and modifications. Some of the more significant changes to this edition include:

- 1. A revised 1998 "Recommendation" which incorporates approved revisions to the registration rules since 1970, including addition of a footnote to define "original" alloy.
- 2. Addition of a table showing the nominal densities for active alloys.

 3. Revised Table of Inactive Alloys to include densitivation datas.
- 3. Revised Table of Inactive Alloys to include deactivation dates.
 4. Revised footnote 19 to expand and clarify reactivation rules.
- 5. Addition of a table listing the chemical composition limits for inactive original alloys.

Since the International Designation System for Wrought Aluminum and Wrought Aluminum Alloys is based on USA's national standard "American National Standard Alloy and Temper Designation System for Aluminum ANSI H35.1," the system limits introduction of experimental alloy compositions to USA registrations. An experimental alloy registered by USA under this system is indicated by the prefix "X" and is subject to the following rules:

- A composition shall not be designated as experimental ("X") for more than five years.
 The "X" is dropped when the alloy is no longer experimental.
- 3. An experimental composition that is inactivated shall retain the prefix "X" for the duration of its inactive status. If reactivated, the "X" shall be removed.

Some of the registered alloys may be the subject of patent or patent applications, and their listing herein is not to be construed in any way as the granting of a license under such patent right.

A list of the organizations that are signatories to the Declaration of Accord on the Recommendation is printed on pages ii-iii.