Date of Issue: March 2019

Affected Publication: API Specification 20E, Alloy and Carbon Steel Bolting for use in the Petroleum and

Natural Gas Industries, Second Edition, February 2017

Addendum 2

Section 2: The following normative reference shall be added to the list:

ANSI/ASME B1.1, Unified Inch Screw Threads, (UN and UNR Thread Form)

Section 2: The following normative reference shall be added to the list:

ISO 17020, Conformity assessment – Requirements for the operation of various types of bodies performing inspection

Section 4.2.2: The following shall be added after the first sentence:

For subcontracted ultrasonic examination, magnetic particle inspection, and liquid penetrant inspection, qualification to ISO 17020 is an acceptable alternative to ISO 17025.

For outsourced NDE services of ultrasonic examination, magnetic particle inspection, and liquid penetrant inspection, qualification to a quality management system in accordance with 5.2.2.1.1 is acceptable.

Section 5.2.2.1.1 shall be replaced with the following:

A quality management system evaluation in accordance with ISO 9001, API Q1, ISO 17020 (for subcontracted NDE only), or ISO 17025 for all BSLs.

Section 5.2.3 a) shall be replaced with the following:

a) BSL-1 Requirements

A quality management system evaluation in accordance with ISO 9001, API Q1, ISO 17020 (for subcontracted NDE only) or ISO 17025.

Section 5.2.3 b) shall be replaced with the following:

b) BSL-2 Requirements

- 1) Requirements specified for BSL-1 are required for BSL-2.
- 2) Onsite process audit performed by a technical authority at an interval no greater than 3 years, or independent or third-party evidence of conformance to the following industry quality standards, as applicable:
 - i. For subcontracted NDE only, ISO 17020 or similar industry recognized quality management system standard (see 5.2.2.1.1) is acceptable.
 - ii. For laboratory services, ISO 17025 is the only acceptable substitute for an onsite process audit or technical evaluation.

Section 5.4.4 g) shall be replaced with:

g) furnace load diagrams or representative photos.

Section 5.4.5.3 shall be replaced with:

Manufacturing processes shall be performed so as to avoid the introduction of stress risers that can occur from sharp angles and tool marks. Threads may be cut or rolled. Unified National Threads shall be "R" (UNR controlled radius series) for external threads and UN for internal threads (ANSI/ASME B1.1).

Section 5.4.6.4 shall be replaced with:

When threads are rolled, parts shall subsequently be stress relieved at a temperature within 50 °F (28 °C) of, but not exceeding, the actual final tempering temperature which is intended to establish mechanical properties. This stress relief requirement is also met if the final temper heat treatment is done after any type of thread forming.

Section 5.4.6.6 shall be replaced with:

Furnace loading diagram or photo shall be prepared for each load configuration.

Alloy and Carbon Steel Bolting for Use in the Petroleum and Natural Gas Industries

API SPECIFICATION 20E SECOND EDITION, FEBRUARY 2017

EFFECTIVE DATE: AUGUST 2017

ADDENDUM 1, SEPTEMBER 2018 ADDENDUM 2, MARCH 2019



Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to ensure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Users of this specification should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 1220 L Street, NW, Washington, DC 20005.

Copyright © 2017 American Petroleum Institute

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, "shall" denotes a minimum requirement in order to conform to the standard.

Should: As used in a standard, "should" denotes a recommendation or that which is advised but not required in order to conform to the standard.

May: As used in a standard, "may" denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, "can" denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 1220 L Street, NW, Washington, DC 20005. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

For API Monogram Program licensees and APIQR Program registrants, this standard shall become effective on the program date printed on the cover but may be used voluntarily from the date of publication.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 1220 L Street, NW, Washington, DC 20005.

Suggested revisions are invited and should be submitted to the Standards Department, API, 1220 L Street, NW, Washington, DC 20005, standards@api.org.