

---

---

---

# AMERICAN NATIONAL STANDARD

## **Performance Criteria for Systems that Estimate the Attenuation of Passive Hearing Protectors for Individual Users**

---

---

---

ANSI/ASA S12.71-2018

Accredited Standards Committee S12, Noise

---

Standards Secretariat  
Acoustical Society of America  
1305 Walt Whitman Road, Suite 300  
Melville, NY 11747

The American National Standards Institute, Inc. (ANSI) is the national coordinator of voluntary standards development and the clearinghouse in the U.S.A. for information on national and international standards.

The Acoustical Society of America (ASA) is an organization of scientists and engineers formed in 1929 to increase and diffuse the knowledge of acoustics and to promote its practical applications.



AMERICAN NATIONAL STANDARD  
**Performance Criteria for Systems that Estimate the  
Attenuation of Passive Hearing Protectors for  
Individual Users**

**Secretariat:**

**Acoustical Society of America**

**Approved on May 7, 2018 by:**

**American National Standards Institute, Inc.**

**Abstract**

This standard pertains to systems intended to estimate the attenuation of hearing protection devices (HPDs) obtained by individual wearers in actual practice. Such systems are designated field attenuation estimation systems (FAESs). This standard provides a classification of FAESs and specifies performance criteria. It also details the evaluation methodology and statistical calculations to be performed on such systems in order to state the uncertainty associated with the individual attenuation estimates that they provide, and specifies a method for computing a personal attenuation rating (PAR). FAES-derived data do not replace the attenuation values from ANSI/ASA S12.6 or the insertion-loss data from ANSI/ASA S12.42, nor are such data suitable for labeling the attenuation of HPDs.

## AMERICAN NATIONAL STANDARDS ON NOISE

The Acoustical Society of America (ASA) provides the Secretariat for Accredited Standards Committees S1 on Acoustics, S2 on Mechanical Vibration and Shock, S3 on Bioacoustics, S3/SC 1 on Animal Bioacoustics, and S12 on Noise. These committees have wide representation from the technical community (manufacturers, consumers, trade associations, organizations with a general interest, and government representatives). The standards are published by the Acoustical Society of America as American National Standards after approval by their respective Standards Committees and the American National Standards Institute (ANSI).

These standards are developed and published as a public service to provide standards useful to the public, industry, and consumers, and to Federal, State, and local governments.

Each of the Accredited Standards Committees (operating in accordance with procedures approved by ANSI) is responsible for developing, voting upon, and maintaining or revising its own Standards. The ASA Standards Secretariat administers Committee organization and activity and provides liaison between the Accredited Standards Committees and ANSI. After the Standards have been produced and adopted by the Accredited Standards Committees, and approved as American National Standards by ANSI, the ASA Standards Secretariat arranges for their publication and distribution.

An American National Standard implies a consensus of those substantially concerned with its scope and provisions. Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered and that a concerted effort be made towards their resolution.

The use of an American National Standard is completely voluntary. Their existence does not in any respect preclude anyone, whether he or she has approved the Standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the Standards.

NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this Standard.



Acoustical Society of America  
Standards Secretariat  
1305 Walt Whitman Road, Suite 300  
Melville, New York 11747  
Telephone: 1 (631) 390-0215  
Fax: 1 (631) 923-2875  
E-mail: [asastds@acousticalsociety.org](mailto:asastds@acousticalsociety.org)

© 2018 by Acoustical Society of America. This standard may not be reproduced in whole or in part in any form for sale, promotion, or any commercial purpose, or any purpose not falling within the provisions of the U.S. Copyright Act of 1976, without prior written permission of the publisher. For permission, address a request to the Standards Secretariat of the Acoustical Society of America.

## Contents

1	Scope .....	1
2	Normative references .....	1
3	Terms and definitions .....	2
4	Types of field attenuation estimation systems .....	3
5	Performance characteristics for FAESs that report a PAR .....	4
5.1	Verification and calibration .....	4
5.2	Maximum permissible ambient noise levels (MPANLs) .....	4
5.3	Maximum test signal exposure levels .....	5
5.4	Assessment of bias and nonlinearity .....	6
5.5	Maximum and minimum measurable attenuation values .....	6
6	Performance characteristics for FAESs that report only pass/fail indicators .....	6
6.1	Verification and calibration .....	6
6.2	Maximum permissible ambient noise levels (MPANLs) .....	6
6.3	Maximum test signal exposure levels .....	7
6.4	Measurement uncertainty for systems that report only pass/fail results .....	7
7	Computation of A-weighted attenuation, $REAT_A$ and $FAES_A$ .....	8
7.1	$REAT_A$ .....	8
7.2	$FAES_A$ .....	9
8	Computation of PAR and its associated uncertainty .....	9
8.1	$PAR_x$ .....	10
8.2	Computation of the principal sources of uncertainty .....	10
9	Experimental data collection for specification of system performance .....	12
9.1	Procedure for FAESs using standard HPDs .....	12
9.2	Procedure for FAESs using surrogate HPDs .....	13
9.3	Procedure for FAESs that report only pass/fail results .....	15
10	Surrogate error for FAESs using surrogate HPDs .....	15
10.1	Computation of surrogate error .....	15
10.2	Statistical test for the surrogate error .....	15
11	Information to be included in user instructions for FAESs .....	16
	Annex A (normative) FAES performance statement .....	17
	Annex B (informative) Equivalence testing to determine MPANLs .....	19
	Annex C (informative) Example assessment of bias and nonlinearity .....	21

Annex D (informative) Example graphical computation of minimum and maximum attenuation values ....	22
Annex E (informative) Example of the computation of measurement uncertainty for a pass/fail FAES.....	24
Annex F (informative) Example of the computation of composite PAR.....	27
F.1 Computation including audiometric data .....	27
F.2 Computation in absence of audiometric data .....	27
F.3 Simplified computation based on lowest-ear PAR .....	28
Annex G (informative) Example of the computation of PAR and its associated uncertainty .....	29
G.1 Computation of PAR and its associated uncertainty .....	29
G.2 Example cases to be used for validation of the computation of PAR and its associated uncertainty .....	32
Annex H (normative) Laboratory-determined values of fitting and spectrum uncertainty.....	34
Bibliography .....	36

## Figures

Figure C.1 – Bland-Altman scatter plot. Each point represents one measurement for a given fit of an HPD using both REAT and a FAES. ....	21
Figure D.1 – Prediction error scatter plot for a physical FAES used to establish the measurable attenuation range. Each point represents one measurement for a given fit of an HPD using both REAT and a FAES. ....	23
Figure E.1 – Pass/fail FAES measurement data and fitted logistic regression function describing the measurement uncertainty. ....	26
Figure F.1 – Example of left and right attenuation as well as the resulting composite attenuation.....	28

## Tables

Table 1 – Types of FAESs .....	4
Table 2 – Octave-band values of the MPANLs corresponding to the lowest FAES test frequency, for earcups with an attenuation of 0 dB. ....	5
Table 3 – Values of $\alpha$ for various protection performance values, $x$ .....	10
Table 4 – Experimental procedure to collect data for FAESs that test standard HPDs .....	13
Table 5 – Experimental procedure to collect data for FAESs that test surrogate HPDs .....	14
Table A.1 – Example performance statement for a FAES that reports a PAR.....	17
Table A.2 – Example performance statement for a FAES that reports a pass/fail rating .....	18
Table B.1 – Illustrative data for a physical FAES.....	19

Table E.1 – REAT <sub>A</sub> (dB) and corresponding FAES <sub>B</sub> outputs for a pass/fail FAES, sorted by increasing values of REAT <sub>A</sub> . The criterion level CRIT for these data is 15.0 dB. Rows containing erroneous measurements are shaded (shading in one row appears inconsistent due to rounding).....	24
Table H.1 – Generic laboratory-determined values of fitting uncertainty ( $u_{\text{fit}}$ ), values in dB.....	34
Table H.2 – Generic laboratory-determined values of spectrum uncertainty ( $u_{\text{spectrum}}$ ), values in dB.....	35