

Access to Additional Content

for

ANSI/ASA S1.18-2010

(Click [here](#) to view the publication)

This Page is not part of the original publication

This page has been added by IHS as a convenience to the user in order to provide access to additional content as authorized by the Copyright holder of this document

Click the link(s) below to access the content and use normal procedures for downloading or opening the files.

➤ [ANSI/ASA S1.18-2010 Software](#)

Information contained in the above is the property of the Copyright holder and all Notice of Disclaimer & Limitation of Liability of the Copyright holder apply.

If you have any questions, or need technical assistance please contact [IHS Support](#).



IHS Additional Content Page

This is a preview. Click here to purchase the full publication.

The American National Standards Institute, Inc. (ANSI) is the national coordinator of voluntary standards development and the clearinghouse in the U.S.A. for information on national and international standards.

The Acoustical Society of America (ASA) is an organization of scientists and engineers formed in 1929 to increase and diffuse the knowledge of acoustics and to promote its practical applications.



AMERICAN NATIONAL STANDARD

**Method for Determining the Acoustic Impedance of
Ground Surfaces**

Secretariat:

Acoustical Society of America

Approved May 28, 2010 by:

American National Standards Institute, Inc.

Abstract

This Standard describes procedures for obtaining the real and imaginary parts of normalized acoustic impedance ratio of ground surfaces from *in-situ* measurements of the sound pressure levels at two vertically separated microphones using specified geometries and the averaged values of the difference between the simultaneous instantaneous sound-pressure signals at the two microphones. It extends and revises the template method given in the 1999 edition to enable the user to obtain values of the normalized specific acoustic impedance ratio of the ground entirely from measurements and independently of any model for the acoustic impedance of the ground surface except as a check on the validity of the resulting values.

AMERICAN NATIONAL STANDARDS ON ACOUSTICS

The Acoustical Society of America (ASA) provides the Secretariat for Accredited Standards Committees S1 on Acoustics, S2 on Mechanical Vibration and Shock, S3 on Bioacoustics, S3/SC 1 on Animal Bioacoustics, and S12 on Noise. These committees have wide representation from the technical community (manufacturers, consumers, trade associations, organizations with a general interest, and government representatives). The standards are published by the Acoustical Society of America as American National Standards after approval by their respective Standards Committees and the American National Standards Institute (ANSI).


These standards are developed and published as a public service to provide standards useful to the public, industry, and consumers, and to Federal, State, and local governments.

Each of the Accredited Standards Committees (operating in accordance with procedures approved by ANSI) is responsible for developing, voting upon, and maintaining or revising its own Standards. The ASA Standards Secretariat administers Committee organization and activity and provides liaison between the Accredited Standards Committees and ANSI. After the Standards have been produced and adopted by the Accredited Standards Committees, and approved as American National Standards by ANSI, the ASA Standards Secretariat arranges for their publication and distribution.

An American National Standard implies a consensus of those substantially concerned with its scope and provisions. Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered and that a concerted effort be made towards their resolution.

The use of an American National Standard is completely voluntary. Their existence does not in any respect preclude anyone, whether he or she has approved the Standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the Standards.

NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this Standard.



Acoustical Society of America
ASA Secretariat
35 Pinelawn Road, Suite 114E
Melville, New York 11747-3177
Telephone: 1 (631) 390-0215
Fax: 1 (631) 390-0217
E-mail: asastds@aip.org

© 2010 by Acoustical Society of America. This Standard may not be reproduced in whole or in part in any form for sale, promotion, or any commercial purpose, or any purpose not falling within the provisions of the U.S. Copyright Act of 1976, without prior written permission of the publisher. For permission, address a request to the Standards Secretariat of the Acoustical Society of America.

[This is a preview. Click here to purchase the full publication.](#)

Contents

1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Measurement method.....	2
4.1	Recommended geometries	2
4.2	Time convention	3
4.3	Measurement procedure	4
4.4	Ground and environmental conditions	4
4.5	Determination of the normalized specific acoustic impedance ratio	5
4.6	Procedure to determine best fit in Step 1	7
4.7	Minimization procedure for Step 2	8
5	Required instruments for measuring ground impedance outdoors	9
5.1	Sound source	9
5.2	Microphones	10
5.3	Calibration	10
5.4	Sound level meter/analyzer.....	10
5.5	Miscellaneous.....	11
5.6	Configuration of measuring system.....	11
5.7	Wind speed	11
6	Measurement.....	11
6.1	Area of ground.....	11
6.2	Data collection.....	11
7	Data reduction	12
7.1	Corrections	12
7.2	Experimental error.....	12
8	Reporting	13
8.1	Introductory information	13
8.2	Documentation of the instrumentation	13
8.3	Meteorological data	13
8.4	Impedance values	13
8.5	Other observations.....	13
9	Templates for obtaining normalized surface impedance model parameters	14
9.1	Templates for the one-parameter impedance model.....	14
9.2	Templates for the two-parameter normalized surface impedance model.....	16
Annex A	(informative) Worked examples of procedure.....	22
A.1	Example 1: Cricket field at the Open University, UK.....	22
A.2	Example 2: Institutional grass at the National Research Council, Canada	27
A.3	Example 3: University lawn in Germany	33

A.4 Example 4: Granite gravel road on U.S. Army Research Laboratory testing facility.....	37
Annex B (informative) Example impedance parameters	40
B.1 One-parameter model	40
B.2 Two-parameter model	40
Annex C (informative) Formulae for the complex sound pressure ratio	41
Annex D (informative) Mathematical functions	43
Annex E (informative) Software for deduction of surface impedance according to ANSI/ASA S1.18-2010.....	46
Bibliography	47

Tables

Table 1 – Template 1A—Pre-calculated level differences (dB) for geometry A using the one- parameter model.....	14
Table 2 – Template 1B—Pre-calculated level differences (dB) for geometry B using the one- parameter model.....	15
Table 3 – Template 2A—Pre-calculated level differences (dB) for geometry A using the two- parameter model.....	16
Table 4 – Template 2B—Pre-calculated level differences (dB) for geometry B using the two- parameter model.....	19
Table A.1 – Cumulative error, E , for the one-parameter templates, computed using Equation (8) in 4.6	23
Table A.2 – Cumulative error, E , for the two-parameter templates, computed using Equation (8) in 4.6	25
Table A.3 – Cumulative error, E , for the one-parameter templates, computed using Equation (8) in 4.6	28
Table A.4 – Cumulative error, E , for the two-parameter templates, computed using Equation (8) in 4.6	28
Table A.5 – Cumulative error, E , for Example 2	34
Table B.1 – Parameter values obtained using one-parameter model	40
Table B.2 – Parameter values obtained using two-parameter model.....	40

Figures

Figure 1 – Geometrical definitions: h_s = source height, h_t = top microphone height, h_b = bottom microphone height, d = source/receiver horizontal separation	3
Figure 2 – Point source and vertically separated microphones at the Open University, UK.....	10
Figure 3b – Template curves for geometry B and eight values of effective flow resistivity, σ_{eff} , between 10 and 3200 kPa s/m ²	15
Figure 4a – Template curves for geometry A with $\alpha_e = 3/\text{m}$ and four values of effective flow resistivity, σ_e (10, 32, 100, and 1000 kPa s/m ²)	17
Figure 4b – Template curves for geometry A with $\alpha_e = 50/\text{m}$ and three values of effective flow resistivity	17
Figure 4c – Template curves for geometry A with $\alpha_e = 100/\text{m}$ and three values of effective flow resistivity, σ_e (10, 100, and 1000 kPa s/m ²)	18
Figure 4d – Template curves for geometry A with $\alpha_e = 250/\text{m}$ and three values of effective flow resistivity, σ_e (10, 100, and 1000 kPa s/m ²)	18
Figure 5a – Template curves for geometry B with $\alpha_e = 3/\text{m}$ and four values of effective flow resistivity, σ_e (10, 32, 100, and 1000 kPa s/m ²)	20
Figure 5b – Template curves for geometry B with $\alpha_e = 50/\text{m}$ and three values of effective flow resistivity	20
Figure 5c – Template curves for geometry B with $\alpha_e = 100/\text{m}$ and three values of effective flow resistivity, σ_e (10, 100, and 1000 kPa s/m ²)	21
Figure 5d – Template curves for geometry B with $\alpha_e = 250/\text{m}$ and three values of effective flow resistivity, σ_e (10, 100, and 1000 kPa s/m ²)	21
Figure A.1 – Template plots for one-parameter impedance model	22
Figure A.2 – Comparisons of measured LD spectra with two-parameter model templates	23
Figure A.3 – Normalized specific acoustic impedance ratio deduced from six sets of averaged complex sound pressure ratios. Those deduced from geometry B are plotted as broken lines. The mean values are plotted as dotted lines.	25
Figure A.4 – A comparison of normalized specific acoustic impedance ratio spectra deduced from Steps 1 and 2 (broken line)	26
Figure A.5 – Template method (Step 1) using data obtained with a single microphone.....	27

Figure A.6 – Template for geometry A and the one-parameter model with superimposed NRC data	27
Figure A.7 – Template for geometry B and the one-parameter model with superimposed NRC data	28
Figure A.8(a) – Template for geometry A and the two-parameter model with superimposed NRC data	29
Figure A.8(b) – Template for geometry A and the two-parameter model with superimposed NRC data	29
Figure A.9(a) – Template for geometry B and the two-parameter model with superimposed NRC data	30
Figure A.9(b) – Template for geometry B and the two-parameter model with superimposed NRC data	30
Figure A.10 – Normalized specific acoustic impedance ratio deduced from the measured complex sound pressure ratios using geometry A.....	31
Figure A.11 – Normalized surface impedance spectra deduced from Step 1 (one-parameter model – solid line, two parameter model – dash and dotted line) and Step 2 (thicker continuous lines)	32
Figure A.12 – Normalized surface impedance spectra deduced from Step 1 (one-parameter model – solid line, two parameter model – dashed lines and dotted line) and Step 2 (thicker continuous lines)	32
Figure A.13 – Data and one-parameter model templates for geometries A and B.....	33
Figure A.14 – Data and 2-parameter model templates for geometries A and B.....	34
Figure A.15 – Deduced normalized surface impedance ratio spectra using all ten measurements	35
Figure A.16 – Smoothed normalized specific acoustic impedance ratio deduced using geometry B.....	36
Figure A.17 – Normalized specific acoustic impedance ratio spectra deduced from both geometries A and B and best-fit impedance model predictions	36
Figure A.18 – ARL data superimposed on one-parameter templates (a) geometry A and (b) geometry B.....	37
Figure A.19 (a) to (h) – ARL Gravel road data superimposed on two-parameter templates.....	38
Figure A.19 a to h (continued) – ARL Gravel road data superimposed on two-parameter templates	39