

BSI Standards Publication

Information technology — Implementation and operation of customer premises cabling

Part 3: Testing of optical fibre cabling



This is a preview. Click here to purchase the full publication.

National foreword

This British Standard is the UK implementation of ISO/IEC 14763-3:2014+A1:2018, incorporating corrigendum March 2015. It supersedes BS ISO/IEC 14763-3:2006+A1:2009, which is withdrawn.

The start and finish of text introduced or altered by amendment is indicated in the text by tags. Tags indicating changes to IEC text carry the number of the IEC amendment. For example, text altered by IEC amendment A1 is indicated by A1.

The start and finish of text introduced or altered by corrigendum is indicated in the text by tags. Text altered by IEC corrigendum March 2015 is indicated in the text by $\boxed{AC_1}$.

The UK participation in its preparation was entrusted to Technical Committee TCT/7/1, Telecommunications - Installation requirements - Cabling infrastructure, design, planning and commissioning.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2018 Published by BSI Standards Limited 2018

ISBN 978 0 580 91917 6

ICS 35.200

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 30 November 2018.

Amendments/corrigenda issued since publication

Date Text affected



ISO/IEC 14763-3

Edition 2.0 2014-06

INTERNATIONAL STANDARD



Information technology – Implementation and operation of customer premises cabling –

Part 3: Testing of optical fibre cabling

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PRICE CODE

G

ICS 35.200 ISBN 978-2-8322-1631-6

Warning! Make sure that you obtained this publication from an authorized distributor.

This is a preview. Click here to purchase the full publication.

CONTENTS

FOF	REWORE)		6		
INT	RODUCT	ON		8		
1	Scope			9		
2	•		es			
3	Terms, definitions and abbreviations					
	3.1	Terms and definitions				
	3.2	Abbreviations				
	3.3	Symbols				
4	Conformance					
5	General requirements					
	5.1	Test system				
	5.2	Reference measurement and calibration				
	5.3	Environme	ental conditions	15		
		5.3.1	Protection of transmission and terminal equipment	15		
		5.3.2	Inspecting and cleaning connectors	15		
		5.3.3	Use of test equipment	15		
		5.3.4	Relevance of measurement	16		
		5.3.5	Treatment of marginal test results	16		
	5.4		ationation			
6	Test equipment					
	6.1	Light sour	ce and power meter	16		
		6.1.1	General			
		6.1.2	Light sources			
		6.1.3	Power meters			
		6.1.4	Test system stability (ffs)			
	6.2					
		6.2.1	General	17		
		6.2.2	OTDR characterization using a launch test cord and a tail test cord	18		
	6.3	Test cords	and adapters			
	0.0	6.3.1	Connecting hardware at test interfaces			
		6.3.2	Reference connector requirements			
		6.3.3	Test cords			
	6.4	MMF laund	ched modal distribution	22		
	6.5	SMF launch condition				
7	Inspecti	on equipme	ent	22		
8	Cabling under test – Channels and permanent links					
	8.1	General				
	8.2	Reference planes				
	8.3	Wavelength of measurement				
	8.4	.4 Direction of measurement				
9	Testing of installed cabling			25		
	9.1 Attenuation					
		9.1.1	LSPM	25		
		9.1.2	OTDR	29		

	9.2	Propaga	Propagation delay			
		9.2.1	Test method	31		
		9.2.2	Treatment of results	32		
	9.3	Length		32		
		9.3.1	Test method	32		
		9.3.2	Measurement uncertainty	32		
		9.3.3	Treatment of results	32		
10	Testing	of cabling	g components within installed cabling	33		
	10.1	_	ion of optical fibre cable			
	10.1	10.1.1	Test method			
		10.1.2	Measurement uncertainty			
		10.1.2	Treatment of results			
	10.2		ion of local and remote test interfaces			
	10.2	10.2.1	Test method			
		10.2.1	Test system measurement uncertainty			
		10.2.2	Treatment of results			
	10.3		ion of connecting hardware			
	10.3		Test method			
		10.3.1 10.3.2				
	10.4		Treatment of results			
	10.4		oss of connecting hardware			
		10.4.1	Test method (in accordance with IEC 61300-3-6, method 2)			
		10.4.2	Treatment of results			
	40.5	10.4.3	Measurement uncertainty			
	10.5	•	ibre length			
		10.5.1	Test method			
		10.5.2	Measurement uncertainty			
		10.5.3	Treatment of results			
	10.6		ion of cords			
		10.6.1	Test method			
		10.6.2	Treatment of results			
11	Inspect	ion of cab	ling and cabling components	42		
	11.1	Optical f	ibre continuity	42		
	11.2	Cabling	polarity	42		
	11.3	Optical fibre cable length4				
	11.4	Inspection of optical fibre end faces				
	11.5	Optical f	ibre core size	43		
Anr	nex A (no	(normative) Launch modal conditions for testing multimode optical fibre				
cab	ling			44		
Anr	nex B (no	ormative)	Visual inspection criteria for connectors	45		
	B.1	Specifies	s optical fibre cabling interfaces	45		
	B.2		ection equipment			
	B.3		oss requirements for cabling interfaces			
		B.3.1	General			
		B.3.2 B.3.3	Multimode cylindrical and rectangular ferrules (20 dB return loss) Single mode PC cylindrical ferrules (35 dB return loss)			
		B.3.4	Single-mode APC cylindrical and rectangular ferrules (60 dB return le			
_						
Anr	nex C (in		Optical time domain reflectometry			
	C.1	Operatio	onal capability	52		
		C.1.1	Effective characterization	52		
		C.1.2	Dynamic range	52		
		This	s is a preview. Click here to purchase the full publication.			
		11110	a promoting to paronage the fair publication.			

	C.1.3	Pulse width	52				
	C.1.4	Integration or sample count	52				
C.2	Limitatio	ons of OTDR capability	53				
	C.2.1	Minimum lengths of operation – Attenuation dead zone	53				
	C.2.2	Ghosting	54				
	C.2.3	Effective group index of refraction	55				
	C.2.4	Backscattering coefficient	55				
Annex D (n	ormative)	Inspection and testing of test and substitution test cords	56				
D.1	General	requirements	56				
D.2	Attenuat	tion (test and substitution test cord reference connections)	56				
		Enhanced three-test-cord and one-test-cord reference methods nel attenuation	58				
E.1	Referen	ce methods for link attenuation	58				
E.2	One-test	-cord method link attenuation 58					
	E.2.1	General	58				
	E.2.2	Test method					
E.3		d three-test-cord reference method for link attenuation					
	E.3.1	General					
	E.3.2	Test method					
Annex F (informative) Quality planning6							
F.1	-	on and test schedules					
F.2	_	inspection and testing					
F.3	ŭ	testing					
	F.3.1	Basic test group					
	F.3.2	Extended test group					
		Examples of calculations of channel and permanent link limits					
G.1		measurement					
G.2		ent link measurement					
ыынодгарп	y		00				
•		ip of related International Standards					
J	•	m and the cabling under test					
Figure 3 –	OTDR char	racterization using a launch test cord and a tail test cord	18				
Figure 4 – A	An example	e of test cord labelling and identification	20				
Figure 5 –	OTDR laun	ich test cord and/or tail test cord schematic	21				
		and permanent links in accordance with A ISO/IEC 11801-1 A rds	23				
Figure 7 –	Channel ar	nd permanent link test configuration	24				
		n of LS-LTC-Near end EQP cord - PM for reference setting					
•		test cord attenuation measurement of installed permanent links					
Figure 10 –	OTDR me	easurement of installed cabling (channel): 2 point attenuation					
		easurement of installed cabling (permanent link)					
•		easurement of optical fibre attenuation					
-		easurement of connection attenuation					
_							
Figure 14 – OTDR measurement of joint attenuation							
•		ation of longth using an OTDP					
rigule 16 –			39				
	11118	s is a preview. Click here to purchase the full publication.					

ISO/IEC 14763-3:2014+AMD1:2018 © ISO/IEC 2018 - 5 -

Figure 17 – OTDR characterization of a SMF permanent link containing a break	40
Figure 18 – OTDR characterization of a permanent link containing a macrobend	41
Figure 19 – Measurement of cord interface attenuation	42
Figure 20 – Connections to channel test for attenuation measurement	26
Figure B.1 – Normal illumination of male MPO	46
Figure B.1 – Normal illumination of male MPO	46
Figure B.3 – Example of multimode LC channel interface	47
Figure B.4 – Example of multimode LC link interface	
Figure B.5 – Example of MPO channel interface	
Figure B.6 – Example of MPO link interface	
Figure B.7 – Example of single-mode LC channel interface	
Figure B.8 – Example of single-mode LC link interface	
Figure B.9 – Example of single-mode LC/APC channel interface	
Figure B.10 – Example of single-mode LC/APC link interface	
Figure B.11 – Example of SM MPO/APC channel interface	
Figure B.12 – Example of SM MPO/APC link interface	
Figure C.1 – OTDR characterization using different length launch test cords	
Figure C.2 – OTDR characterization showing ghost effects	
Figure C.3 – OTDR characterization showing complex ghost effects	5
Figure D.1 – Measurement of launch test cord, tail test cord and substitution test cord interface attenuation	56
Figure E.1 – Connection of LS – LTC – PM for reference setting	
Figure E.2 – Connections to link for attenuation measurement	
Figure E.3 – Connection of LS – LTC – PM for reference setting	
Figure E.4 – Connection of LTC – STC – TTC for enhanced three-test-cord verification	
Figure E.5 – Connections to link for attenuation measurement	60
Table 1 – MMF light source characteristics	17
Table 2 – SMF light source characteristics	17
Table 3 – Non-LC reference connector requirements	19
Table 4 – Connecting hardware attenuation	28
Table B.1 – Inspection requirements for cabling interfaces with 20 dB return loss	47
Table B.2 – Inspection requirements for cabling interfaces with 35 dB return loss	
Table B.3 – Inspection requirements for cabling interfaces with 60 dB return loss	
Table C.1 – Default effective group IOR values	
Table C.2. Default backscattering coefficient values	55

INTERNATIONAL ELECTROTECHNICAL COMMISSION

INFORMATION TECHNOLOGY – IMPLEMENTATION AND OPERATION OF CUSTOMER PREMISES CABLING –

Part 3: Testing of optical fibre cabling

FOREWORD

- 1) ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.
- 2) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees and ISO member bodies.
- 3) IEC, ISO and ISO/IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO, IEC or ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.
- 5) ISO and IEC do not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. ISO or IEC are not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC National Committees or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC Publication or any other IEC, ISO or ISO/IEC publications.
- 8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this ISO/IEC Publication may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

International Standard ISO/IEC 14763-3 was prepared by subcommittee 25: Interconnection of information technology equipment, of ISO/IEC joint technical committee 1: Information technology.

This second edition cancels and replaces the first edition published in 2006 and its Amendment 1:2009.

This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

This is a preview. Click here to purchase the full publication.