



BSI Standards Publication

Power transformers

Part 18: Measurement of frequency response

NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

raising standards worldwide™

This is a preview. [Click here to purchase the full publication.](#)

National foreword

This British Standard is the UK implementation of EN 60076-18:2012. It is identical to IEC 60076-18:2012.

The UK participation in its preparation was entrusted to Technical Committee PEL/14, Power transformers.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2013

Published by BSI Standards Limited 2013

ISBN 978 0 580 69776 0

ICS 29.180

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 January 2013.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

**Power transformers -
Part 18: Measurement of frequency response
(IEC 60076-18:2012)**

Transformateurs de puissance -
Partie 18: Mesure de la réponse
en fréquence
(CEI 60076-18:2012)

Leistungstransformatoren -
Teil 18: Messung des
Frequenzübertragungsverhaltens
(IEC 60076-18:2012)

This European Standard was approved by CENELEC on 2012-08-13. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Management Centre: Avenue Marnix 17, B - 1000 Brussels

Foreword

The text of document 14/718/FDIS, future edition 1 of IEC 60076-18, prepared by IEC/TC 14 "Power transformers" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 60076-18:2012.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2013-05-13
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2015-08-13

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard IEC 60076-18:2012 was approved by CENELEC as a European Standard without any modification.

CONTENTS

1	Scope	7
2	Terms and definitions	7
3	Purpose of frequency response measurements	8
4	Measurement method	9
4.1	General	9
4.2	Condition of the test object during measurement	10
4.3	Measurement connection and checks	11
4.3.1	Measurement connection and earthing	11
4.3.2	Zero-check measurement	11
4.3.3	Repeatability check	11
4.3.4	Instrument performance check	11
4.4	Measurement configuration	12
4.4.1	General	12
4.4.2	Principles for choosing the measurement configuration	12
4.4.3	Star- and auto-connected windings with a neutral terminal	13
4.4.4	Delta windings and other windings without an accessible neutral	13
4.4.5	Zig-zag connected windings	14
4.4.6	Two-winding three-phase transformers	14
4.4.7	Three-phase auto-transformers	14
4.4.8	Phase shifting transformers	14
4.4.9	Reactors	14
4.4.10	Method for specifying additional measurements	14
4.5	Frequency range and measurement points for the measurement	15
5	Measuring equipment	15
5.1	Measuring instrument	15
5.1.1	Dynamic range	15
5.1.2	Amplitude measurement accuracy	16
5.1.3	Phase measurement accuracy	16
5.1.4	Frequency range	16
5.1.5	Frequency accuracy	16
5.1.6	Measurement resolution bandwidth	16
5.1.7	Operating temperature range	16
5.1.8	Smoothing of recorded data	16
5.1.9	Calibration	16
5.2	Measurement leads	16
5.3	Impedance	17
6	Measurement records	17
6.1	Data to be recorded for each measurement	17
6.2	Additional information to be recorded for each set of measurements	18
	Annex A (normative) Measurement lead connections	20
	Annex B (informative) Frequency response and factors that influence the measurement	23
	Annex C (informative) Applications of frequency response measurements	37

Annex D (informative) Examples of measurement configurations	39
Annex E (informative) XML data format.....	43
Bibliography.....	44
Figure 1 – Example schematic of the frequency response measurement circuit.....	10
Figure A.1 – Method 1 connection.....	21
Figure A.2 – Method 3 connection.....	22
Figure B.1 – Presentation of frequency response measurements	23
Figure B.2 – Comparison with a baseline measurement	24
Figure B.3 – Comparison of the frequency responses of twin transformers	24
Figure B.4 – Comparison of the frequency responses from sister transformers	25
Figure B.5 – Comparison of the frequency responses of three phases of a winding.....	25
Figure B.6 – General relationships between frequency response and transformer structure and measurement set-up for HV windings of large auto-transformer	27
Figure B.7 – Effect of tertiary delta connection on the frequency response of a series winding	28
Figure B.8 – Effect of star neutral connection on the tertiary winding response	29
Figure B.9 – Effect of star neutral termination on series winding response	29
Figure B.10 – Measurement results showing the effect of differences between phases in internal leads connecting the tap winding and OLTC	30
Figure B.11 – Effect of measurement direction on frequency response	30
Figure B.12 – Effect of different types of insulating fluid on frequency response	31
Figure B.13 – Effect of oil filling on frequency response	31
Figure B.14 – Effect of a DC injection test on the frequency response	32
Figure B.15 – Effect of bushings on frequency response	32
Figure B.16 – Effect of temperature on frequency response	33
Figure B.17 – Examples of bad measurement practice	34
Figure B.18 – Frequency response of a tap winding before and after partial axial collapse and localised inter-turn short-circuit with a photograph of the damage	34
Figure B.19 – Frequency response of an LV winding before and after axial collapse due to clamping failure with a photograph of the damage [8].....	35
Figure B.20 – Frequency response of a tap winding with conductor tilting with a photograph of the damage [1]	36
Figure D.1 – Winding diagram of an auto-transformer with a line-end tap changer	40
Figure D.2 – Connection diagram of an inductive inter-winding measurement on a three-phase YNd1 transformer.....	41
Figure D.3 – Connection diagram for a capacitive inter-winding measurement on a three-phase YNd1 transformer	42
Figure D.4 – Connection diagram for an end-to-end short-circuit measurement on a three-phase YNd1 transformer.....	42
Table 1 – Standard measurements for a star connected winding with taps	13
Table 2 – Standard measurements for delta connected winding without tap	14
Table 3 – Format for specifying additional measurements	15
Table D.1 – Standard end-to-end measurements on a three-phase auto-transformer	39
Table D.2 – Tap-changer connections.....	40