

Screw Conveyors for Bulk Materials

ANSI/CEMA Standard No. 350 Fifth Edition

Published by the Conveyor Equipment Manufacturers Association

DISCLAIMER

The information provided herein is advisory only.

These recommendations provided by CEMA are general in nature and are not intended as a substitute for professional advice. Users should seek the advice, supervision and/or consultation of qualified engineers, safety consultants, and other qualified professionals.

Any use of this publication, or any information contained herein, or any other CEMA publication is made with the agreement and understanding that the user and the user's company assume full responsibility for the designs, safety, specifications, suitability and adequacy of any conveyor system, system component, mechanical or electrical device designed or manufactured using this information.

The user and the user's company understand and agree that CEMA, its member companies, its officers, agents and employees are not and shall not be liable in any manner under any theory of liability to anyone for reliance on or use of these recommendations. The user and the user's companies agree to release, hold harmless and indemnify and defend CEMA, its member companies, successors, assigns, officers, agents and employees from any and all claims of liability, costs, fees (including attorney's fees), or damages arising in any way out of the use of this information.

CEMA and its member companies, successors, assigns, officers, agents and employees make no representations or warranties whatsoever, either expressed or implied, about the information contained herein, including, but not limited to, representations or warranties that the information and recommendations contained herein conform to any federal, state or local laws, regulations, guidelines or ordinances.

Conveyor Equipment Manufacturers Association

5672 Strand Ct., Suite 2 Naples, Florida 34110 www.cemanet.org

CEMA Screw Conveyor Engineering Committee of the Engineering Conference Copyright 2019 / All rights reserved.

ISBN: 978-1-891171-64-2

Summary of Changes

CEMA's Screw Conveyor for Bulk Materials was first published in 1971 and currently the 5th edition, 2nd Printing with cosmetics changes only in 2019. Following are the summary of changes that have occurred in the 5th edition 1st and 2nd Printing:

- 1. Dimensions for 30" and 36" Screws were added in the following Tables: Chapter 2, Tables 2-3, 2-5, 2-7, 2-8, and 2-9 Chapter 3, Tables 3-2 and 3-5
- 2. Most drawings and figures were updated with color CAD drawings
- 3. Metric Practice in Screw Conveyor Calculations for Tables M-1 & M-2 in Appendix.

Safety Notice

The Conveyor Equipment Manufacturers Association (CEMA) has developed industry Standard Safety Labels for use on the conveying equipment of its member companies. The purpose of the labels is to identify common and uncommon hazards, conditions, and unsafe practices that can injure, or cause the death of, the unwary or inattentive person who is working at or around conveying equipment. The labels are available for sale to member companies and nonmember companies.

A full description of the labels, their purpose, and guidelines on where to place the labels on typical equipment, has been published in CEMA's Safety Label Brochure (No. 201). The brochure is available for purchase by members and nonmembers of the Association.

PLEASE NOTE: Should any of the safety labels supplied by the equipment manufacturer become unreadable for any reason, the equipment USER is then responsible for replacement and location of these safety labels.

Replacement labels and placement guidelines can be obtained by contacting your equipment supplier or CEMA.

A CEMA DVD safety instruction video, A/V 6, titled *Screw Conveyor, Drag Conveyor, and Bucket Elevator Safety DVD*, has also been developed by the CEMA Screw Conveyor Section. It describes key safety practices people should adhere to when working with and around these different conveyors. It is available for purchase from CEMA.

NOTE: Some pictures and diagrams of screw conveyors in this book are without covers or have exposed screws or shafting and are for illustration purposes only. Conveyors should never be used without covers, guards, or protective equipment.

Contents

CHAPTER 1 Screw Conveyor History and General Application

Screw conveyor history. Discussion of application of screw conveyors. Data needed in preparation of screw conveyor design. Illustrations of screw conveyor installations.

CHAPTER 2 Bulk Material Characteristics, Material Code, Conveyor Size and Speed, Component Groups 9

Discussion and codification of bulk material characteristics. Tables of bulk materials. Screw conveyor sizes, speeds and capacities. Lump size limitations. Enumeration and description of screw conveyor components. Component specifications for normal, heavy and extra heavy service.

CHAPTER 3 Horsepower Requirements, Torsional Ratings for Conveyor Screws, End Thrust, Typical Horizontal Screw Conveyor Problem 37

Formula for horsepowers of horizontal screw conveyors. Torsional rating of conveyor screws and all screw parts. Horsepower limitation charts for conveyor screws based on bolted couplings. Screw conveyor end thrust. Deflections of conveyor screws. Detailed solution of typical horizontal screw conveyor problem.

CHAPTER 4 Screw Conveyor Layout, Screw Conveyor Components

Instructions for layout of screw conveyors with dimensional data. Discharge arrangements described and illustrated. Detail data on screw conveyor components such as screws, flighting, modifications to flighting, troughs, discharge spouts and gates, trough ends, trough end bearings, trough end seals, trough covers, hangers and hanger bearings, shafting, bolts and trough supports.

53

CHAPTER 5 Materials of Construction, Classes of Enclosure, Weld Finish, Special Features and Modifications, Installation, Operation, Maintenance, Expansion 75

Discussion of materials of construction. Codification of classes of enclosure. Description and codification of weld finishes. Description and illustration of special features of conveyor components for various purposes. Directions for installing screw conveyors, operating them and preventive maintenance. Calculation of the expansion of screw conveyors handling hot materials.

Calculations

CHAPTER 6 Screw Feeders, Single and Multiple 105 Description of single and multiple screw feeders, their uses and limitations, speeds, capacities, arrangements with extension conveyors, horsepowers required. Bin bottom type multiple screw feeders. Also included is guidance on Variable Frequency Drive (VFD) selection for screw feeders. **CHAPTER 7** Inclined and Vertical Screw Conveyors 118 Discussion of capacity versus angle of incline and other factors concerning inclined screw conveyors, including horsepower. Description of vertical screw conveyors, their speeds, capacities, components and horsepowers required. **CHAPTER 8** Screw Conveyor Drives, Drive Efficiencies and Drive Service Factors 129 Discussion and illustration of horizontal, inclined and vertical screw conveyor drives. Table of drive efficiencies. Service factor references. **APPENDIX** Derivation of Horsepower Formula for Horizontal Screw Conveyors, Individual Torsional Ratings of Conveyor Screw Parts, Metric Practice in Screw Conveyor

INDEX

159

139

Foreword

While the screw conveyor as we know it today is the descendant of the oldest form of conveyor in recorded history, utilizing the oldest mechanical device employed by mankind, the inclined plane (wrapped around a core to form a helix), this book is the first attempt to bring together the collective knowledge and experience of leading manufacturers to codify what has come to be acceptable engineering practice for the benefit of user and manufacturer alike.

The Screw Conveyor Engineering Committee of the CEMA (Conveyor Equipment Manufacturers Association) Engineering Conference was assigned the task of bringing together under one cover the accumulated experience of many individuals and their companies in an effort to provide a common basis for the selection and installation of screw conveyors of sizes and capacities to handle the most commonly encountered bulk materials of commerce and industry.

This book is not intended as the final word on all screw conveyor engineering, but rather to serve as an engineering guide. Those who have contributed so generously of time and effort to its compilation strongly recommend that help from conveyor manufacturers be enlisted to check selection of sizes, capacities and types of conveyors where there is the least element of doubt, and always when materials of unknown, unusual or changeable character are involved. Today's rapidly changing technology and the continuous introduction of new materials—or old materials with new characteristics—emphasizes this recommendation as a means to the satisfactory performance of a conveyor or conveyor system.

The Conveyor Equipment Manufacturers Association believes that this publication represents a milestone in the long historical development of the screw conveyor as a vital machine for the transport of a wide variety of materials.

NOTE: Environmental as well as many other conditions vary with each installation. As a result, this engineering manual is intended merely as a guide to conveyor selection. Neither the Conveyor Equipment Manufacturers Association nor its member companies warrant that adherence to the guidelines set forth in this brochure will necessarily result in proper selection, manufacture, installation or maintenance of conveyor equipment and/or a conveyor system. Unless there are specific written specifications or recommendations pursuant to a written contractual commitment, the Conveyor Equipment Manufacturers Association and its member companies hereby disclaim all responsibility for any equipment and/or system malfunction, any violations of law, property damage, personal injury or any other damages resulting from equipment and/or system selection, design, installation, maintenance, or operation carried out by the contractor or user.

Nomenclature

The following list covers the symbols used in this book:

| Area, (in²) |
|--|
| Cross-sectional area of coupling bolt, (in ²) |
| Projected area of pipe and bushing bolt hole, (in ²) |
| Coupling bolt hole diameter, (in) |
| Capacity, (ft³/hr) |
| Capacity factor |
| Screw feeder capacity, (ft ³ /hr) at 1 RPM |
| Coefficient of linear expansion, (in/in per °F) |
| Diameter, (in) |
| Coupling shaft diameter, (in) |
| Pipe diameter, (in) |
| Conveyor screw diameter, (in) |
| Modulus of elasticity |
| Combined efficiency of drive motor and reduction gear |
| Hanger bearing factor |
| Conveyor diameter factor |
| Flight factor |
| Material factor |
| Overload factor |
| Paddle factor |
| Empirical vertical screw conveyor factor |
| Horsepower |
| Friction horsepower of empty feeder conveyor |
| Friction horsepower of material only, in feeder conveyor |
| Friction horsepower of empty screw conveyor |
| Friction horsepower of material only, in a screw conveyor |
| , Horsepower to convey material vertically |
| Moment of inertia |
| Polar moment of inertia |
| Percent of trough loading, expressed decimally |
| Length, (ft) |
| Feeder conveyor length, (ft) |
| Length, (in) |
| |

- Equivalent length of feeder, (ft) L,
- lbf Pounds per force
- Ν Speed of conveyor, RPM
- n Number of coupling bolts at each end of screw section
- Ρ Pitch of screw flight, (in)
- Pounds per square inch psi
- R Ratio of lump sizes
- RPM Revolutions per minute
- Load radius, (in) r
- S Allowable working stress, (psi)
- S₁ Allowable shear stress in coupling bolts, (psi)
- **S**₂ Allowable bearing stress for coupling bolts, pipe and bushing, (psi)
- S_3^{-} Allowable shear stress in pipe, (psi)
- S_4 Allowable shear stress of unhardened coupling, (psi)
- S₅ T Allowable shear stress of hardened coupling, (psi)
 - Torque, (in-lbs)
- T₁ Torsional shear rating of coupling bolts, (in-lbs)
- T_2^1 Torsional bearing rating of coupling bolts, (in-lbs)
- T_3^2 Torsional rating of pipe, (in-lbs)
- T₄ Torsional rating of unhardened coupling, (in-lbs)
- T₅ Torsional rating of hardened coupling, (in-lbs)
- Higher of any two temperatures, (°F) t₁
- Lower of any two temperatures, (°F) t_2
- Weight or apparent density of material, (lb/ft³) W
- Weight of a section, part or piece, (lbs) w
- Polar section modulus of pipe or coupling shaft Zp

(Page intentionally blank)

CHAPTER 1

Screw Conveyor History and General Application

Screw Conveyor History Application of Screw Conveyors Design Preparation Illustrations

Screw Conveyor History

If we overlook the possibility that some caveman used some round tree branches under a rock to replace sliding friction by rolling friction, thereby inventing the roller conveyor, undoubtedly the first conveyor as such was designed by Archimedes (287 to 212 B.C.)—Greek mathematician, physicist and inventor—for removing water from the hold of a ship built for King Hiero of Syracuse. Apparently the idea was a success, for this same device was next used to raise water from a river to irrigate farm land.

The Archimedean conveyor was of the internal helical screw type. It was mounted at an angle with its lower end in the water and the upper end arranged to discharge the water to a flume or irrigation ditch. The device was powered by a slave who turned a crank fixed to its upper end. Even in contemporary times a similar machine is said to have been used in the Netherlands—except for the substitution of electrical power for muscle power. In modern industry, the Archimedean screw exists in the form of a tubular conveyor, to the inner surface of which is fastened a helical ribbon. The exterior of the tube is supported on rolls, and the tube is revolved by a pinion meshing with an externally mounted ring gear.

It is said that Archimedes may have been the originator of two other forms of screw conveyors. One, a tube formed into a helix around a central shaft or core; the other, a helix rotating within a stationary casing, is the forerunner of the modern screw conveyor in its most common form.

A little before 1790, an American inventor, John Fitch, designed a steam boat to be propelled by a section of screw conveyor flighting that appears in the drawings of that day to be almost identical to flighting used in present day screw conveyors. It appears, though, that this method of ship propulsion was at once a victim of technological obsolescence brought on by the success of paddle wheels. The term, "screw," still lives on as the usual terminology for a ship's propeller.

During the many centuries of individual or small group self-sufficiency following the days of Archimedes, there was little need for continuous mechanical handling devices because there was little need for volume production, and even if there had been, there was no satisfactory source of power available.

It was about 1900 years later that screw conveyors again were proposed, when it became imperative that some means be found to handle mechanically the grain harvests made necessary to serve the needs of the rapidly growing American population. In 1783, the man who might be called the patron saint of mechanized materials handling, Oliver Evans, laid out on paper his first mechanized flour mill which incorporated not only screw conveyors but bucket elevators and belt conveyors as well. All these devices were tied together by a system of wooden toothed gears, wooden pulley and leather belts, and all were driven from a single water wheel.

The first mill built by Evans in 1785 actually was a reconstruction of a 1742 mill thought by some to have been built by his grandfather. The screw conveyor as first designed by Evans consisted of a round wooden core on which were mounted in helical form a series of wooden plows or flattened wooden pegs. The whole screw assembly revolved in a wooden trough or "box" as it was called then. Appropriate sliding gates in the trough bottom could be opened to deliver grain to the mills as needed. Soon, though, Evans improved on his design by making the screws of helically formed sheet metal sections mounted on a wooden core that might be anywhere from five to twenty feet long. He still maintained his trough of "close fitting" boards.