CGA C-1-2009

METHODS FOR PRESSURE TESTING COMPRESSED GAS CYLINDERS

TENTH EDITION



COMPRESSED GAS ASSOCIATION, INC. 4221 Walney Road, 5th Floor Chantilly, VA 20151 Phone: 703-788-2700 Fax: 703-961-1831 E-mail: cga@cganet.com

PLEASE NOTE:

The information contained in this document was obtained from sources believed to be reliable and is based on technical information and experience currently available from members of the Compressed Gas Association, Inc. and others. However, the Association or its members, jointly or severally, make no guarantee of the results and assume no liability or responsibility in connection with the information or suggestions herein contained. Moreover, it should not be assumed that every acceptable commodity grade, test or safety procedure or method, precaution, equipment or device is contained within, or that abnormal or unusual circumstances may not warrant or suggest further requirements or additional procedure.

This document is subject to periodic review, and users are cautioned to obtain the latest edition. The Association invites comments and suggestions for consideration. In connection with such review, any such comments or suggestions will be fully reviewed by the Association after giving the party, upon request, a reasonable opportunity to be heard. Proposed changes may be submitted via the Internet at our web site, <u>www.cganet.com</u>.

This document should not be confused with federal, state, provincial, or municipal specifications or regulations; insurance requirements; or national safety codes. While the Association recommends reference to or use of this document by government agencies and others, this document is purely voluntary and not binding unless adopted by reference in regulations.

A listing of all publications, audiovisual programs, safety and technical bulletins, and safety posters is available via the Internet at our website at <u>www.cganet.com</u>. For more information contact CGA at Phone: 703-788-2700, ext. 799. E-mail: <u>customerservice@cganet.com</u>.

Work Item 10-018 Cylinder Specifications Committee

NOTE—Due to the extensive changes in this document, technical changes from the previous edition are not identified.

NOTE—Appendices A, C, D, E, and F (Informative) are for information only.

NOTE—Appendix B (Normative) is a requirement.

TENTH EDITION: 2009 NINTH EDITION: 2006 EIGHTH EDITION: 2004 SEVENTH EDITION: 1996

© 2009 The Compressed Gas Association, Inc. All rights reserved.

All materials contained in this work are protected by United States and international copyright laws. No part of this work may be reproduced or transmitted in any form or by any means, electronic or mechanical including photocopying, recording, or any information storage and retrieval system without permission in writing from The Compressed Gas Association, Inc. All requests for permission to reproduce material from this work should be directed to The Compressed Gas Association, Inc., 4221 Walney Road, Suite 500, Chantilly VA 20151. You may not alter or remove any trademark, copyright or other notice from this work.

Pade

		-			
1	Introduction	1			
2	Scope	1			
3	Definitions	1			
3	Deminitions	1			
4	Overview	3			
	4.1 Water jacket method	3 3			
	4.2 Direct expansion method	3			
	4.4 Regulatory approval of cylinder regualifiers	4			
	4.5 Visual inspection of cylinders at time of requalification	4			
5	Water jacket method	4			
Ū	5.1 Scope	4			
	5.2 Requirements	6			
	5.3 Test system components	8			
	5.4 Calibrated cylinder	11			
	5.5 Lest system accuracy verification	12			
	5.6 Test procedure	1/			
	5.7 Cylinder relesting	14			
6	Direct expansion method	15			
	6.1 Scope	15			
	6.2 Test system components	17			
	6.3 Calibrated cylinder	/ ا			
	6.5 Test system accuracy verification	18			
	6.6 Test procedure				
_					
7	Proof pressure method	22			
	7.1 Scope	22			
	7.2 Test system components	23			
	7.4 Test procedures	24			
0		05			
8	8 References				
Fig	jures				
Fig	ure 1-Typical schematic diagram of water jacket test apparatus	5			
Fig	ure 2—Total expansion	6			
Fig	ure 3-Permanent expansion	6			
Fig	ure 5—Adjustment of water level in burette for expansion readings	/			
Fig	ure 6—Example of a burette-style FID requirements				
Fig	jure 7—Typical nonburette EID systems	10			
Fig	ure 8—Typical micro processor-based EID systems	10			
Fig	ure 9—Typical schematic diagram of direct expansion test apparatus	16			
Fig	ure 10—Factors for compressibility of water	21			
Fig	jure 11—Typical schematic diagram of liquid-based proof pressure test apparatus	22			
Ap	pendices				
Ap	pendix A—Sources of regulatory information (Informative)	27			
Ap	pendix B—Test system component calibration (Normative)	28			
Ар	pendix C-Marking of cylinders requalified by the water jacket or direct expansion methods (Informative	e).30			
Appendix D—Sample forms for cylinder requalification (Informative)					
Ap	pendix E— I roubleshooting (Informative)	35			
н		40			

Appendix figures

Figure C-1—Example of DOT cylinder marking	31
Figure C-2—Example of TC cylinder marking	31
Appendices tables	
Table D-1—Test apparatus calibration verification data for water jacket volumetric expansion testing	32
Table D-2—Direct expansion hydrostatic requalifying of cylinders	33
Table D-3—Regualification data sheet	34
Table F-1—Checklist for accuracy verification of test system (Direct expansion method)	40
Table F-2—Checklist for determining the expansion of test system and components	
(Direct expansion method)	41
Table F-3—Checklist for hydrostatic testing of cylinders (Direct expansion method)	42

1 Introduction

Pressure testing of compressed gas cylinders is required for many newly manufactured cylinders and also is an accepted test method for the requalification of cylinders. The referenced edition of the applicable documents, as specified by the U.S. Department of Transportation (DOT) in Title 49 of the U.S. *Code of Federal Regulations* (49 CFR), in Canada by Transport Canada (TC) in CSA B339, *Cylinders, Spheres, and Tubes for the Transportation of Dangerous Goods*, as referenced by the *Transportation of Dangerous Goods Regulations*, or the authority having jurisdiction, shall be available at each facility conducting pressure testing/requalification [1, 2, 3].

For the testing/requalification of cylinders manufactured under an exemption/special permit or permit, a current copy of that exemption or permit shall also be available. (See Appendix A for addresses of agencies that produce these documents).

2 Scope

This standard contains operating and equipment requirements necessary to properly perform pressure testing of compressed gas cylinders.

3 Definitions

For the purpose of this standard, the following definitions apply.

3.1 Accuracy

Degree of conformity of a measured or calculated quantity to its actual (true) value.

3.2 Accuracy grade

Inherent quality of the device.

NOTE—Accuracy grade expresses the maximum error allowed for the device at any reading and is expressed as a percentage of the full scale of the device.

3.3 Actual test pressure

True, recorded pressure applied to a cylinder during a test.

3.4 Bar

Metric measurement used for marking service pressure (1 bar = 14.5 psi).

3.5 Calibration

Process of adjusting a device to match a known standard so that it indicates to within specified accuracy limits.

NOTE—See Appendix B for information on calibration devices.

3.6 Calibration verification

Checking of an individual device or test apparatus by comparison with a given standard to determine the indication error at specified points of the scale.

3.7 Calibrated cylinder

Cylinder that has certified calibration points of pressure with corresponding expansion values.

NOTE—It is a secondary, derived standard used for the verification and demonstration of test system accuracy and integrity.

3.8 Condemn

Determination that a cylinder is unserviceable for continued transportation of dangerous goods and that the cylinder may not be restored by repair, rebuild, requalification, or other procedures.

3.9 Cylinder

Any type of pressure vessel designed for a minimum internal pressure of 276 kPa, abs (2.8 bar, abs, 40 psia) and used for transportation of compressed gases that is required by the regulatory authority to be pressure tested.¹

3.10 Defect

An imperfection requiring a cylinder to be rejected or condemned.

3.11 Elastic expansion

Temporary increase in cylinder's volume due to application of pressure that is lost when pressure is released.

NOTE—The calculation for elastic expansion is total expansion minus permanent expansion.

3.12 Error

Difference between the indicated value and the true value of the variable being measured.

3.13 Expansion indicating device (EID)

Device used to directly or indirectly measure the expansion of a cylinder during the test.

3.14 Hydrostatic test

Method of pressure testing a cylinder using liquid as the pressurization media.

3.15 Independent Inspection Agency

Inspection firm approved by DOT as outlined in 49 CFR 107.803 [1].

3.16 Master gauge

Pressure indicating device (PID) used as a calibration standard that has an accuracy grade equal to or better than the requirement for the PID in the test apparatus.

3.17 Percent permanent expansion

Ratio of permanent expansion to total expansion, expressed as a percentage.

NOTE—The calculation for percent permanent expansion is permanent expansion divided by total expansion times 100.

3.18 Periodic retest

Test performed at an interval prescribed by a regulatory body as a part of the requalification.

3.19 Permanent expansion

Increase in cylinder volume due to application of pressure that is not recovered when pressure is released.

3.20 Pneumatic test

Method of pressure testing a cylinder using gas as the pressurization media.

3.21 Pressure indicating device (PID)

Device used to measure the pressure applied to a cylinder during the test.

3.22 Proof pressure test

Cylinder testing procedure consisting of an application of internal pressure without measurement of the cylinder expansion.

3.23 Reference gauge

PID used in the daily verification of a proof test system that has an accuracy grade equal to or better than the requirement for the PID to be checked.

NOTE—Also known as referee gauge.

¹ kPa shall indicate gauge pressure unless otherwise noted as (kPa, abs) for absolute pressure or (kPa, differential) for differential pressure. All kPa values are rounded off per CGA P-11, *Metric Practice Guide for the Compressed Gas Industry* [4].