



American National Standard for

Rotodynamic Pumps

for Vibration Measurements and
Allowable Values

ANSI/HI 9.6.4-2016



6 Campus Drive
First Floor North
Parsippany, New Jersey
07054-4406
www.Pumps.org

This is a preview. [Click here to purchase the full publication.](#)

This page intentionally blank.

American National Standard for

Rotodynamic Pumps

for Vibration Measurements and
Allowable Values

Sponsor
Hydraulic Institute
www.Pumps.org

Approved November 7, 2016
American National Standards Institute, Inc.

American National Standard

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgement of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the secretariat or sponsor whose name appears on the title page of this standard.

CAUTION NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this standard. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute.

Published By

Hydraulic Institute
6 Campus Drive, First Floor North
Parsippany, NJ 07054-4406
www.Pumps.org

Copyright © 2016 Hydraulic Institute
All rights reserved.

No part of this publication may be reproduced in any form,
in an electronic retrieval system or otherwise, without prior
written permission of the publisher.

Printed in the United States of America

ISBN 978-1-935762-54-6



Recycled
paper

This is a preview. [Click here to purchase the full publication.](#)

Contents

Page

Foreword	v
9.6.4 Rotodynamic pumps for vibration measurements and allowable values	1
9.6.4.1 Introduction and scope	1
9.6.4.1.1 Introduction	1
9.6.4.1.2 Scope	1
9.6.4.2 Bearing housing vibration measurement	2
9.6.4.2.1 Measurement procedure and units	2
9.6.4.2.2 Vibration measurement instrumentation and transducers	3
9.6.4.2.3 Measurement locations and directions	4
9.6.4.2.4 Vibration acceptance tests	4
9.6.4.2.5 Allowable pump bearing housing vibration	7
Appendix A Test report (informative)	11
Appendix B Factors affecting vibration (informative)	13
B.1 Residual mechanical unbalance of rotating parts	13
B.2 Residual mechanical unbalance of rotating parts - abrasive fluids	17
B.3 Pump and driver natural frequency and resonance	17
B.4 Miscellaneous mechanical problems	17
B.5 Hydraulic disturbances	18
B.6 Hydraulic resonance in piping	18
B.7 Managing vibration of vertical structures	19
Appendix C Guideline for motor vibration for vertical pumps (informative)	20
C.1 Introduction and recommendation	20
C.2 Background	21
Appendix D Vibration source identification chart (informative)	22
Appendix E Vibration transducer mounting and sensitivity (informative)	23
Appendix F Vibration transducer types (informative)	25
Appendix G Index	27
Figures	
9.6.4.2.2.2 — Mounting methods for vibration transducers	4
9.6.4.2.3.1 — Measurement locations and directions	5
9.6.4.2.5.1a — Allowable pump vibration, pump types BB and OH	8
9.6.4.2.5.1b — Allowable pump vibration, pump types VS1, VS2, VS3, VS4, VS5, VS6, VS7, and VS8	8
9.6.4.2.5.1c — Allowable pump vibration, solids-handling pump types	9
9.6.4.2.5.1d — Allowable pump vibration, horizontal and vertical slurry pump types (excluding wet pit cantilever belt-driven pumps with overhung motors)	9
B.1 — Center of gravity displacement or acceptable residual unbalance (balance grade G6.3) – metric units	14
B.2 — Center of gravity displacement or acceptable residual unbalance (balance grade G6.3) – US customary units	15