



American National Standard for

Rotodynamic Pumps

for Nomenclature and Definitions



HYDRAULIC
INSTITUTE

American National Standard for
Rotodynamic Pumps
for Nomenclature and Definitions

Sponsor
Hydraulic Institute
www.Pumps.org

Approved April 9, 2019
American National Standards Institute, Inc.

American National Standard

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgement of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the secretariat or sponsor whose name appears on the title page of this standard.

CAUTION NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this standard. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute.

Published By

Hydraulic Institute, Inc.
6 Campus Drive, First Floor North
Parsippany, NJ 07054-4406
www.Pumps.org

Copyright © 2019 Hydraulic Institute
All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of the publisher.

Printed in the United States of America
ISBN 978-1-935762-79-9



Recycled
paper

Contents

Page

Foreword xi

14.1 Types and nomenclature 1

 14.1.1 Introduction 1

 14.1.1.1 Purpose 1

 14.1.1.2 Scope 1

 14.1.2 Definition of rotodynamic pump 2

 14.1.3 Types of rotodynamic pumps 2

 14.1.3.1 Overhung impeller type (OH) 2

 14.1.3.1.1 Flexibly coupled (OH0, OH1, OH2, OH3, and OH6). 4

 14.1.3.1.2 Rigidly coupled/short coupled (OH4 and OH13) 4

 14.1.3.1.2.1 Rigidly coupled 4

 14.1.3.1.2.2 Short-coupled 4

 14.1.3.1.3 Close-coupled (OH5, OH6, OH7, and OH8). 4

 14.1.3.1.3.1 High-speed integral, gear-driven pumps (OH6) 4

 14.1.3.2 Impeller between-bearing type (BB). 5

 14.1.3.2.1 One and two stage with axially split casing (BB1) 5

 14.1.3.2.2 One and two stage with radially split casing (BB2). 5

 14.1.3.2.3 Multistage with axially split casing and volute (BB3). 6

 14.1.3.2.4 Multistage with radially split casing held in place with tie bolts (BB4). 6

 14.1.3.2.5 Multistage with radially split casing external casing and internal pumping
 elements (BB5). 6

 14.1.3.3 Impeller vertically suspended type (VS). 6

 14.1.3.3.1 Single casing 8

 14.1.3.3.1.1 Submersible (VS0) 8


 14.1.3.3.1.2 Discharge through column (VS1, VS2, and VS3) 8

 14.1.3.3.1.3 Separate Discharge (VS4 and VS5) 8

 14.1.3.3.2 Double casing (VS6, VS7, and VS8). 8

 14.1.3.4 Regenerative turbine type (RT) 8

 14.1.3.5 Circulator pumps (CP) 9



14.1.3.5.1.1	Close-coupled circulator pumps (CP1 and CP2)	10
14.1.3.5.1.2	Flexibly coupled circulator pumps (CP3).	10
14.1.3.6	Hydraulic power recovery turbine.	10
14.1.3.7	Pumps of other configurations	10
14.1.3.7.1	Casing/Impeller Types.	12
14.1.3.7.1.1	Diffuser, vaned (a).	12
14.1.3.7.1.3	Volute (b).	12
14.1.3.7.1.4	Axial (c).	12
14.1.3.7.1.5	Pitot Tube (d).	12
14.1.3.7.2	Vertical	12
14.1.3.7.2.1	In-line (std)	12
14.1.3.7.2.2	End Suction (g)	12
14.1.3.7.3	Self-priming (h)	12
14.1.3.7.4	Sealless (i)	13
14.1.3.7.4.1	Magnetic Drive	13
14.1.3.7.4.3	Canned motor	13
14.1.3.7.5	Multistage (j)	13
14.1.3.7.6	Rotodynamic pump types – overhung impeller.	14
14.1.3.7.7	Rotodynamic pump types – vertically suspended.	15
14.1.3.7.8	Rotodynamic pump types – between bearing.	15
14.1.3.7.9	Rotodynamic pump types – regenerative turbine	15
14.1.3.7.10	Rotodynamic pump types – circulator pump.	16
14.1.4	Impeller Designs	16
14.1.4.1	Specific speed (n_s), type number (K), and suction specific speed (S)	18
14.1.4.1.1	Specific Speed	18
14.1.4.1.2	Type Number	18
14.1.4.1.3	Suction Specific Speed.	19
14.1.4.2	Radial flow	20
14.1.4.3	Francis vane (modified radial flow).	20
14.1.4.4	Mixed flow.	20
14.1.4.5	Axial flow	21

14.1.4.6	Vortex (recessed impeller) type	21
14.1.5	Discharge casing design	21
14.1.5.1	Volute	22
14.1.5.2	Concentric (circular) casing	22
14.1.5.2.1	Modified concentric casing	22
14.1.5.3	Vaned diffuser/collector	22
14.1.5.3.1	Bowl and stage casing	22
14.1.6	Construction drawings	22
14.1.7	General information	62
14.1.7.1	Size of a rotodynamic pump	62
14.1.7.2	Definition of duplicate performance pump	63
14.1.7.3	Definition of dimensionally interchangeable pump	63
14.1.7.4	Definition of identical pump (performance and dimensional)	63
14.1.7.5	Definitions for major pump sub-assemblies	63
14.1.7.5.1	Overhung pumps	63
14.1.7.5.1.1	Liquid end (or wet end assembly)	63
14.1.7.5.1.2	Power end (or frame assembly)	64
14.1.7.5.1.3	Back pull-out assembly	64
14.1.7.5.1.4	Bare rotor	65
14.1.7.5.1.5	Rotating assembly	65
14.1.7.6	Bowl assembly	65
14.1.7.7	Position of casing	65
14.1.7.8	Rotation of shaft	66
14.1.7.8.1	Gear driven	67
14.1.7.8.2	Double-extended shaft	67
14.1.7.9	Special case ASME/ANSI B73.1, C-frame adapter	67
14.1.7.10	Drivers for vertically suspended pumps	68
14.1.7.10.1	Vertical solid shaft driver	68
14.1.7.10.2	Vertical hollow shaft driver	68
14.1.7.11	Open/enclosed line shaft	68
14.1.7.12	Vertically suspended pump length	69

14.1.7.12.1	Total pump length	69
14.1.7.12.2	Pump setting	69
14.1.8	Pump nomenclature.	70
14.1.8.1	Definitions - part names	70
14.1.8.2	Overhung and between-bearing pump dimensions	80
14.2	Definitions, terminology, and symbols	86
14.2.1	Volume rate of flow (Q)	89
14.2.1.1	BEP rate of flow (Q_{opt})	89
14.2.1.2	Minimum continuous stable flow ($Q_{min\ all\ stable}$)	90
14.2.1.3	Minimum continuous thermal flow ($Q_{min\ thermal}$)	90
14.2.1.4	Maximum allowable flow ($Q_{max\ all}$)	90
14.2.2	Speed (n)	90
14.2.2.1	Maximum allowable continuous speed ($n_{max\ all}$)	90
14.2.2.2	Minimum allowable continuous speed ($n_{min\ all}$)	90
14.2.2.3	Rated speed (n_r)	90
14.2.3	Head (h) [H]	90
14.2.3.1	Gauge head (h_g) [H_{Mx}]	90
14.2.3.2	Velocity head (h_v)	90
14.2.3.3	Elevation head (Z) [H_{stat}]	91
14.2.3.4	NPSH datum plane.	91
14.2.3.5	Total suction head (h_s), open suction	91
14.2.3.6	Total suction head (h_s), closed suction	91
14.2.3.7	Total discharge head (h_d)	92
14.2.3.8	Total head (H) [H_{tx}]	92
14.2.3.9	Bowl assembly total head (H_{ba})	92
14.2.3.10	Atmospheric head (h_{atm})	92
14.2.3.11	Friction head (h_f or h_j)	92
14.2.4	Condition points	93
14.2.4.1	Rated condition point (Q_r) or (H_r)	93
14.2.4.2	Specified condition point	93
14.2.4.3	Normal condition point (Q_N) or (H_N)	93

14.2.4.4	Best efficiency point (BEP)	93
14.2.4.5	Shutoff (SO)	93
14.2.4.6	Operating regions	93
14.2.4.6.1	Preferred operating region (POR)	93
14.2.4.6.2	Allowable operating region (AOR)	93
14.2.5	Suction conditions	94
14.2.5.1	Submerged suction	94
14.2.5.2	Flooded suction	94
14.2.5.3	Static suction lift (l_s)	94
14.2.5.4	Net positive suction head (NPSH)	94
14.2.5.5	Net positive suction head available (NPSHA)	94
14.2.5.6	Net positive suction head required (NPSHR)	94
14.2.5.7	Net positive suction head resulting in 3% loss of total head (NPSH3)	94
14.2.5.8	Maximum suction pressure ($p_{s\ max}$) [$p_{1\ max\ op}$ or $p_{1\ max\ all}$]	95
14.2.6	Power	95
14.2.6.1	Electric motor input power (P_{mot}) [P_1]	95
14.2.6.2	Pump input power (P_p) [P]	95
14.2.6.3	Bowl assembly input power (P_{ba})	95
14.2.6.4	Pump output power (P_w) [P_u]	95
14.2.6.5	Overall efficiency (η_{OA})	95
14.2.6.6	Pump efficiency (η_p)	96
14.2.6.7	Bowl assembly efficiency (η_{ba})	96
14.2.6.8	Pump pressures	96
14.2.6.8.1	Working pressure (pd) [$p2\ max\ op$]	96
14.2.6.8.2	Maximum allowable working pressure (MAWP)	96
14.2.6.8.3	Field-test pressure	96
14.2.6.8.4	Rated discharge pressure	96
14.2.6.9	Impeller balancing	96
14.2.6.9.1	Single-plane balancing (formerly called static balancing)	96
14.2.6.9.2	Two-plane balancing (formerly called dynamic balancing)	96

Appendix A97

Appendix B98

Appendix C105

Appendix D107

Figures

14.1.3 — Rotodynamic pump types2

14.1.3.7 — Typical vertical pump impeller types with rings (casing and/or impeller).17

14.1.4.1 — General impeller types20

14.1.4.2 — Double suction radial flow impeller20

14.1.4.4 — Mixed-flow impeller21

14.1.4.5 — Axial-flow impeller.21

14.1.4.6 — Vortex (recessed impeller) type.21

14.1.6a — Overhung impeller – flexibly coupled – frame mounted – single stage23

14.1.6b — Overhung impeller – flexibly coupled – frame mounted – single-stage – lined pump24

14.1.6c — Overhung impeller – flexibly coupled – horizontal – axial flow – single-stage25

14.1.6d — Pitot tube pump26

14.1.6e — Overhung impeller – flexibly coupled – foot mounted – single-stage – stock pump27

14.1.6f — Overhung impeller – flexibly coupled – foot mounted – single-stage28

14.1.6g — Overhung impeller – flexibly coupled – foot mounted – single-stage – ASME B73.129

14.1.6h — Overhung impeller – flexibly coupled – foot mounted – self-priming – single-stage30

14.1.6i — Overhung impeller – flexibly coupled – centerline mounted – single-stage – API 61031

14.1.6j — Overhung impeller – flexibly coupled – vertical – in-line – integral bearing frame – single-stage32

14.1.6k — Overhung impeller – flexibly coupled – vertical – end suction – single-stage33

14.1.6l — Overhung impeller – rigidly coupled – vertical – in-line – single-stage34

14.1.6m — Overhung impeller – close-coupled – vertical – in-line – single-stage (showing seal and packing) ...35

14.1.6n — Overhung impeller – close-coupled – vertical – end suction – single-stage – vertically mounted36

14.1.6o — Overhung impeller – close-coupled – high-speed integral gear – single-stage37

14.1.6p — Overhung impeller – close-coupled – horizontal – single -stage – end suction38

14.1.6q — Overhung impeller – close-coupled – submersible – diffuser – single-stage – end suction.39

14.1.6r — Overhung impeller – close-coupled – submersible – volute – single-stage – end suction40

14.1.6s — Between bearings – single-stage – axially split pump41

14.1.6t — Between bearings – single-stage – radially split pump.42

14.1.6u — Between bearings – multistage – axially split pump43

14.1.6v — Between bearings – multistage – radially split – single casing pump44

14.1.6w — Between bearings – multistage – radially split – double casing pump	45
14.1.6x — Regenerative turbine – overhung side channel	46
14.1.6y — Regenerative turbine – overhung peripheral	47
14.1.6z — Regenerative turbine – between bearings - peripheral	48
14.1.6aa — Close-coupled sealless with canned motor	49
14.1.6bb — Close-coupled horizontal in-line.	49
14.1.6cc — Flexibly coupled horizontal in-line.	50
14.1.6dd — Vertically suspended – single casing – submersible pump	51
14.1.6ee — Vertically suspended – single casing – discharge through column – deep-well (set) pumps.	52
14.1.6ff — Vertically suspended – single casing – discharge through column – short-set pump	53
14.1.6gg — Vertically suspended – single casing – discharge through column – short-set - mixed flow pump . . .	54
14.1.6hh — Vertically suspended – single casing – discharge through column – volute pump	55
14.1.6ii — Vertically suspended – single casing – discharge through column – axial flow pump	56
14.1.6jj — Vertically suspended – single casing – separate discharge – line shaft pump.	57
14.1.6kk — Vertically suspended – single casing – separate discharge – cantilever pump	58
14.1.6ll — Vertically suspended – double casing – diffuser pump.	59
14.1.6mm — Vertically suspended – double casing – volute/diffuser multistage pump	60
14.1.6nn — Vertically suspended – double casing – volute multistage pump.	61
14.1.6oo — Vertically suspended – in-line casing diffuser	62
14.1.7.5.1.1 — Liquid end (or wet end) assembly	63
14.1.7.5.1.2 — Power end (or frame assembly)	64
14.1.7.5.1.3 — Back pull-out assembly	65
14.1.7.7 — Position of casing and shaft rotation	66
14.1.7.8a — Horizontal pump – shaft rotation (CW rotation).	66
14.1.7.8b — Vertical pump – shaft rotation (CW rotation).	67
14.1.7.9 — Pump with C-frame motor adapter, short coupled	68
14.1.7.12 — Vertically suspended pump dimensions	69
14.1.8.2a — Overhung impeller – flexibly coupled – single-stage – frame mounted.	80
14.1.8.2b — Overhung impeller – flexibly coupled – single-stage – frame mounted – pump on base plate	81
14.1.8.2c — Overhung impeller – flexibly coupled – single-stage – centerline mounted	81
14.1.8.2d — Overhung impeller – flexibly coupled – single-stage – centerline mounted – pump on baseplate . . .	82
14.1.8.2e — Overhung impeller – flexibly coupled – single-stage – centerline mounted (top suction)	82
14.1.8.2f — Overhung impeller – flexibly coupled – single-stage – centerline mounted – pump on baseplate (top suction)	83
14.1.8.2g — Impeller between bearings – flexibly coupled – single-stage – axial (horizontal) split case – pump on baseplate.	83

14.1.8.2h — Impeller between bearings – flexibly coupled – single-stage – axial (horizontal) split case	84
14.1.8.2i — Overhung impeller – close-coupled – single-stage – end suction	84
14.1.8.2j — Overhung impeller – flexibly coupled – vertical – end suction – single-stage – separate driver support.	85
14.1.8.2k — Overhung impeller – flexibly coupled – vertical – end suction – single-stage – integral driver support	85
14.1.8.2l — Overhung impeller – close-coupled – single-stage – vertical end suction	86
14.2.3.4 — Datum elevation for various pump designs at eye of first-stage impeller	91
14.2.4.6.2 — Performance curve for rotodynamic pumps	93
B.1 — Dimensions for types JM and JP, alternating current, face-mounting, close-coupled pump motors having rolling element contact bearings. (This figure relates to Tables B.1 and B.2.)	100
B.4 — Standard dimensions for HI – NEMA type HP and HPH vertical, solid-shaft motors	103
B.5 — Standard dimensions for HI – NEMA vertical hollow-shaft motors	104

Tables

14.1.1 – Rotodynamic pump type designations cross reference	1
14.1.3.1 – Rotodynamic pump types – overhung	3
14.1.3.2 – Rotodynamic pump types - between-bearing	5
14.1.3.3 – Rotodynamic pump types - vertically suspended	7
14.1.3.4 – Rotodynamic pump types – regenerative turbine type	9
14.1.3.5 – Rotodynamic pump types – circulator pumps.	9
14.1.3.7 – Rotodynamic pump sub-classifications	11
14.1.8.1a – Rotodynamic pump nomenclature - alphabetical listing	70
14.1.8.1b – Rotodynamic pump nomenclature - numerical listing.	78
14.2a – Principal symbols	86
14.2b – Subscripts.	88
B.3 – provides open drip-proof frame selections.	98
B.1 – Dimensions for type JM, alternating current, face-mounting, close-coupled pump motors (US customary units)	99
B.2 – Dimensions for type JP, alternating current, face-mounting, close-coupled pump motors (US customary units)	100
B.2 – Dimensions for type JP, alternating current, face-mounting, close-coupled pump motors (US customary units)	101
B.3 – Open drip-proof frame selections.	101
B.4 – Standard dimensions for HI – NEMA type HP and HPH vertical solid-shaft motors (US customary units)	102
B.5 – Dimensions for vertical hollow-shaft driver couplings (US customary units)	103