



American National Standard for

Rotodynamic Vertical Pumps

of Radial, Mixed, and Axial Flow
Types for Nomenclature and
Definitions

ANSI/HI 2.1-2.2-2014



6 Campus Drive
First Floor North
Parsippany, New Jersey
07054-4406
www.Pumps.org

This is a preview. [Click here to purchase the full publication.](#)

This page intentionally blank.

American National Standard for

Rotodynamic Vertical Pumps

of Radial, Mixed, and Axial Flow Types
for Nomenclature and Definitions

Sponsor
Hydraulic Institute
www.Pumps.org

Approved April 8, 2014
American National Standards Institute, Inc.

American National Standard

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgement of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the secretariat or sponsor whose name appears on the title page of this standard.

CAUTION NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this standard. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute.

Published By

Hydraulic Institute
6 Campus Drive, First Floor North
Parsippany, NJ 07054-4406
www.Pumps.org

Copyright © 2014 Hydraulic Institute
All rights reserved.

No part of this publication may be reproduced in any form,
in an electronic retrieval system or otherwise, without prior
written permission of the publisher.

Printed in the United States of America

ISBN 978-1-935762-14-0



Recycled
paper

This is a preview. [Click here to purchase the full publication.](#)

Contents

Page

Foreword	v
2 Rotodynamic vertical pumps	1
2.1 Types and nomenclature	1
2.1.1 Scope	1
2.1.2 Definition of rotodynamic vertical pumps	1
2.1.3 Types of vertical pumps	1
2.1.4 Classification by configuration	11
2.1.5 Classification by impeller design	16
2.1.6 General information	19
2.2 Definitions, terminology, and symbols	28
2.2.1 Rate of flow (capacity) (Q or q) [Q]	30
2.2.2 Speed (n)	31
2.2.3 Head (h) [H]	31
2.2.4 Condition points	34
2.2.5 Suction conditions	35
2.2.6 Power	36
2.2.7 Pump pressures	37
2.2.8 Impeller balancing	37
2.2.9 Rotodynamic vertical pump icons – vertically suspended	37
Appendix A Hollow-shaft driver	43
Appendix B Index	45
Figures	
2.1.3 — Vertical pump types – vertically suspended rotor – single and multistage	2
2.1.3.1 — Vertical, multistage, submersible pump (VS0)	3
2.1.3.2 — Deep-well pumps (VS1)	4
2.1.3.3a — Vertical single or multistage, short setting, open line shaft (VS1)	5
2.1.3.3b — Mixed flow vertical — open line shaft (VS1)	6
2.1.3.3c — Vertical double suction, short setting, open line shaft (VS2)	7
2.1.3.3d — Vertical, axial flow impeller (propeller) type (enclosed line shaft) below-floor discharge configuration(VS3)	8
2.1.3.4a — Line-shaft design sump pump (VS4)	9
2.1.3.4b — Cantilever shaft design sump pump (VS5)	10
2.1.3.5a — Vertical, single, or multistage diffuser (double casing) barrel or can pump (VS6)	12
2.1.3.5b — Vertical double suction, single or multistage barrel or can pump (VS7)	13
2.1.3.5c — Vertical, multistage volute (double casing) barrel or can pump (VS7a)	14
2.1.3.6 — Vertical in-line casing diffuser pump (VS8)	15

2.1.4.4 — Typical vertical pump impeller types with rings (casing and/or impeller)	17
2.1.5.5a — General vertical pump characteristic curves	20
2.1.5.5b — General vertical pump impeller configuration and specific speeds	20
2.1.6.6.1 — Pump length	27
2.2.3.4 — Datum elevation for various pump designs at eye of first-stage impeller	33
2.2.4.6 — Typical performance curve for rotodynamic pumps of lower specific speed design	34
2.2.9.1.1.1 — Submersible turbine (VS0)	38
2.2.9.1.2.1 — Discharge through column – diffuser – wet pit (VS1)	38
2.2.9.1.2.2 — Discharge through column – volute – wet pit (VS2)	39
2.2.9.1.2.3 — Discharge through column – axial flow – wet pit (VS3)	39
2.2.9.1.3.1 — Separate discharge – line shaft – vertical sump (VS4)	40
2.2.9.1.3.2 — Separate discharge – cantilever (VS5)	40
2.2.9.2.1 — Vertically suspended – double casing – double suction – diffuser (VS6)	41
2.2.9.2.2a — Vertically suspended – double casing - volute - diffuser (VS7)	41
2.2.9.2.2b — Vertical volute multistage double casing pump (VS7a)	41
2.2.9.3.1 — Vertically suspended – in-line casing – multistage diffuser (VS8)	42
A.1 — Vertical hollow-shaft driver coupling dimensions	44
Tables	
2.1.6.5 — Alphabetical part name listing	21
2.2a — Principal symbols	28
2.2b — Subscripts	30

Foreword (Not part of Standard)

Purpose and aims of the Hydraulic Institute

The purpose and aims of the Institute are to promote the continued growth and well-being of pump users and manufacturers and further the interests of the public in such matters as are involved in manufacturing, engineering, distribution, safety, transportation, and other problems of the industry, and to this end, among other things:

- a) To develop and publish standards for pumps;
- b) To collect and disseminate information of value to its members and to the public;
- c) To appear for its members before governmental departments and agencies and other bodies in regard to matters affecting the industry;
- d) To increase the amount and to improve the quality of pump service to the public;
- e) To support educational and research activities;
- f) To promote the business interests of its members but not to engage in business of the kind ordinarily carried on for profit or to perform particular services for its members or individual persons as distinguished from activities to improve the business conditions and lawful interests of all of its members.

Purpose of Standards

- 1) Hydraulic Institute Standards are adopted in the public interest and are designed to help eliminate misunderstandings between the manufacturer, the purchaser, and/or the user and to assist the purchaser in selecting and obtaining the proper product for a particular need.
- 2) Use of Hydraulic Institute Standards is completely voluntary. Existence of Hydraulic Institute Standards does not in any respect preclude a member from manufacturing or selling products not conforming to the Standards.

Definition of a Standard of the Hydraulic Institute

Quoting from Article XV, Standards, of the By-Laws of the Institute, Section B:

“An Institute Standard defines the product, material, process or procedure with reference to one or more of the following: nomenclature, composition, construction, dimensions, tolerances, safety, operating characteristics, performance, quality, rating, testing and service for which designed.”

Comments from users

Comments from users of this standard will be appreciated, to help the Hydraulic Institute prepare even more useful future editions. Questions arising from the content of this standard may be directed to the Technical Director of the Hydraulic Institute. The inquiry will then be directed to the appropriate technical committee for provision of a suitable answer.

If a dispute arises regarding contents of an Institute standard or an answer provided by the Institute to a question such as indicated above, the point in question shall be sent in writing to the Technical Director of the Hydraulic Institute, who shall initiate the appeals process.

Revisions

The Standards of the Hydraulic Institute are subject to constant review, and revisions are undertaken whenever it is found necessary because of new developments and progress in the art. If no revisions are made for five years, the standards are reaffirmed with the *ANSI Essential Requirements*.

Units of measurement

Metric units of measurement are used, and corresponding US customary units appear in brackets. Charts, graphs, and sample calculations are also shown in both metric and US customary units. Since values given in metric units