



American National Standard for

Rotodynamic (Vertical) Pumps

for Nomenclature and Definitions

ANSI/HI 2.1-2.2-2008



6 Campus Drive
First Floor North
Parsippany, New Jersey
07054-4406
www.Pumps.org

This page intentionally blank.

American National Standard for

Rotodynamic (Vertical) Pumps

for Nomenclature and Definitions

Sponsor
Hydraulic Institute
www.Pumps.org

Approved September 10, 2008
American National Standards Institute, Inc.

American National Standard

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgement of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the secretariat or sponsor whose name appears on the title page of this standard.

CAUTION NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this standard. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute.

Published By

Hydraulic Institute
6 Campus Drive, First Floor North
Parsippany, NJ 07054-4406
www.Pumps.org

Copyright © 2008 Hydraulic Institute
All rights reserved.

No part of this publication may be reproduced in any form,
in an electronic retrieval system or otherwise, without prior
written permission of the publisher.

Printed in the United States of America

ISBN 978-1-880952-85-6



Recycled
paper

Hydraulic Institute Standards, Copyright © 1997-2009, All Rights Reserved

This is a preview. [Click here to purchase the full publication.](#)

Contents

	Page
Foreword	v
2 Rotodynamic (vertical) pumps	1
2.1 Types and nomenclature	1
2.1.1 Scope	1
2.1.2 Definition of rotodynamic (vertical) pumps	1
2.1.3 Types of vertical pumps	1
2.1.4 Classification by configuration	13
2.1.5 Classification by impeller design	13
2.1.6 General information	16
2.2 Definitions, terminology, and symbols	22
2.2.1 Rate of flow (capacity) (Q or q) [Q]	25
2.2.2 Speed (n)	25
2.2.3 Head (h) [H]	26
2.2.4 Condition points	28
2.2.5 Suction conditions	29
2.2.6 Power	30
2.2.7 Pump pressures	31
2.2.8 Impeller balancing	31
2.2.9 Rotodynamic (vertical) pump icons – vertically suspended	32
Appendix A Hollow shaft driver	37
Appendix B Index	39
Figures	
2.1.3 — Vertical pump types – vertically suspended – single and multistage	2
2.1.3.1 — Deep well pumps (VS1)	3
2.1.3.2a — Vertical single or multistage, short setting, open lineshaft (VS1)	4
2.1.3.2b — Mixed flow vertical — open lineshaft (VS1)	5
2.1.3.2c — Vertical double suction, short setting, open lineshaft (VS2)	6
2.1.3.2d — Vertical, axial flow impeller (propeller) type (enclosed lineshaft) below floor discharge configuration (VS3)	7
2.1.3.3a — Vertical, single, or multistage diffuser (double casing) barrel or can pump (VS6)	8
2.1.3.3b — Vertical double suction, single or multistage barrel or can pump (VS7)	9
2.1.3.3c — Vertical, multistage volute (double casing) barrel or can pump (VS7a)	10
2.1.3.4 — Vertical in-line casing diffuser pump (VS8)	11
2.1.3.5 — Vertical, multistage, submersible pump (VS0)	12
2.1.4.4 — Wearing ring arrangements	14
2.1.5.5 — General impeller types	17

2.2.3.4 — Datum elevation for various pump designs at eye of first-stage impeller	27
2.2.4.6 — Typical performance curve for rotodynamic pumps.	29
2.2.9.1.1.1 — Submersible turbine (VS0)	32
2.2.9.1.2.1 — Discharge through column – diffuser – wet pit (VS1)	32
2.2.9.1.2.2 — Discharge through column – volute – wet pit (VS2)	33
2.2.9.1.2.3 — Discharge through column – axial flow – wet pit (VS3)	33
2.2.9.1.3.1 — Separate discharge – lineshaft – vertical sump (VS4).	34
2.2.9.1.3.2 — Separate discharge – cantilever (VS5)	34
2.2.9.2.1 — Vertically suspended – double casing – double suction – diffuser (VS6).	35
2.2.9.2.2a — Vertically suspended – double casing - volute - diffuser (VS7)	35
2.2.9.2.2b — Vertical volute multistage double casing pump (VS7a)	35
2.2.9.3.1 — Vertically suspended – in-line casing – multistage diffuser (VS8)	36
A.1 — Vertical hollow shaft driver coupling dimensions.	38

Tables

2.1.6.5 — Alphabetical part name listing	18
2.2a — Principal symbols	22
2.2b — Subscripts	24