



NEUTRAL-SUPPORTED POWER CABLE ASSEMBLIES
WITH
WEATHER-RESISTANT EXTRUDED INSULATION
RATED 600 VOLTS

Publication # ICEA S-76-474-2000

© 2000 by

INSULATED CABLE ENGINEERS ASSOCIATION, Inc.

STANDARD FOR
NEUTRAL-SUPPORTED POWER CABLE ASSEMBLIES
WITH
WEATHER-RESISTANT EXTRUDED INSULATION
RATED 600 VOLTS

Publication #ICEA S-76-474-2000

Published By
INSULATED CABLE ENGINEERS ASSOCIATION, Inc.
Post Office Box 440
South Yarmouth, Massachusetts 02664, U.S.A.

Approved June 8, 2000 by
INSULATED CABLE ENGINEERS ASSOCIATION, Inc.

© Copyright 2000 by the Insulated Cable Engineers Association, Inc. All rights including translation into other languages, reserved under the Universal Copyright Convention, the Berne Convention for the Protection of Literary and Artistic Works, and the international and Pan American Copyright Conventions.

FOREWORD

ICEA publications are adopted in the public interest and are designed to eliminate misunderstanding between the manufacturer and user and to assist the user in selecting and obtaining proper products for his particular need. Existence of an ICEA publication does not in any respect preclude the manufacture or use of products not conforming to the publication.

The user of this publication is cautioned to observe any applicable health or safety regulations and rules relative to the manufacture and use of cable made in conformity with this publication. This publication hereafter assumes that manufacture, testing, installation and maintenance of cables defined by this publication will be performed only by properly trained personnel using suitable equipment.

Questions of interpretation of ICEA publications can only be accepted in writing at Headquarters by the Secretary, and the reply shall be provided in writing.

Suggestions for improvements in this publication are welcome, and should be sent to ICEA at the address below.

INSULATED CABLE ENGINEERS ASSOCIATION, INC.

Post Office Box 440
South Yarmouth, MA 02664 USA
Telephone: (508) 394-4424

Copies of this publication may be obtained from:

Global Engineering Documents
15 Inverness Way East
Englewood, CA 80112 USA
Telephone: (800) 854-7179 or (303) 397-7956
E Mail: global@his.com
<http://global.his.com>

TABLE OF CONTENTS

Section	Page
PART I. GENERAL	
1.1 Scope	1
1.2 Assemblies	1
1.3 Design Options	1
1.4 Operating Conditions	2
1.4.1 Normal Service Operation Temperature	2
1.4.2 Emergency Overload Operation Temperature	2
1.4.3 Short Circuit Operation Temperature	2
1.4.4 Rated Voltage	2
1.5 Testing and Test Frequency	3
1.6 Test Methods	3
PART 2. COMPONENT CHARACTERISTICS AND REQUIREMENTS	
2.0 General	5
2.1 Physical and Electrical Properties	5
2.1.1 Aluminum	5
2.1.2 Copper	5
2.2 Phase Conductors	6
2.2.1 Aluminum Phase Conductors	6
2.2.2 Copper Phase Conductors	6
2.3 Neutral Conductors	6
2.3.1 Aluminum Alloy 6201-T81	6
2.3.2 Aluminum 1350	7
2.3.3 Aluminum Conductor, Coated-Steel Reinforced (ACSR)	7
2.3.4 Aluminum Conductor, Aluminum-Clad Steel Reinforced (ACSR/AW)	7
2.3.5 Hard Drawn Copper	7
2.3.6 Copper and Copper-Clad Steel Composite	7
2.3.7 Coated Steel Wires	7
2.4 Conductor Size Units	7
2.5 Bare Neutral Conductor Size Determination	8
2.6 Conductor Diameter	8
2.7 Binders	8
2.7.1 Options	8

Section	Page
PART 3 INSULATION	
3.1 Insulation or Covering	14
3.1.1 75 °C Normal Service Operation Insulation	14
3.1.2 90 °C Normal Service Operation Insulation	14
3.1.3 Alternate Insulation	14
3.2 Neutral Coverings	14
3.3 Binder Coverings	14
3.3.1 Covering	14
3.3.2 Covering Thickness	15
3.4 Separator	15
3.5 Electrical Requirements	15
3.5.1 Voltage Tests	15
3.6 Insulation or Neutral Covering Requirements	16
3.6.1 Thickness Requirements	16
3.6.2 Physical Requirements	16
PART 4 CABLE ASSEMBLIES AND IDENTIFICATION	
4.1 Cable Assemblies	18
4.1.1 Twisted Assemblies	18
4.1.2 Parallel Assemblies	18
4.1.3 S-Z Assemblies (Reverse Twist)	18
4.2 Manufacturer Identification (Optional)	18
PART 5 PERFORMANCE REQUIREMENTS FOR FINISHED CABLE	
5.0 General	19
5.1 Strength of Neutral Conductors	19
5.2 Completed Assembly Neutral Conductor Strength Tests	19
5.3 Maximum Phase Conductor dc Resistance per Unit Length	19
5.3.1 Direct Measurement of Phase Conductor dc Resistance Per Unit Length	20
5.3.2 Calculation of Phase Conductor dc Resistance Per Unit Length	20
PART 6 TEST METHODS FOR INSULATION OR COVERINGS	
6.1 Methods for Measuring Insulation Physical and Air Oven Aging Properties	21
6.2 Method for Measuring Insulation Heat Deformation (Distortion)	21
6.3 Method for Measuring Insulation Hot Creep	21
6.4 Method for Measuring Absorption Coefficient	21