



STANDARD FOR
CONCENTRIC NEUTRAL CABLES
RATED 5,000 - 46,000 VOLTS

Publication # ICEA S-94-649-2000

© 2001 by

INSULATED CABLE ENGINEERS ASSOCIATION, INC.

**STANDARD FOR
CONCENTRIC NEUTRAL CABLES
RATED 5,000 - 46,000 VOLTS**

Standard #
ICEA S-94-649-2000

Published By
INSULATED CABLE ENGINEERS ASSOCIATION, Inc.
Post Office Box 440
South Yarmouth, Massachusetts 02664, U.S.A.
© January 2001

Approved September 6, 2000 by
INSULATED CABLE ENGINEERS ASSOCIATION, Inc.
Approved July 3, 2000 by AEIC
Approved

© 2001 by

INSULATED CABLE ENGINEERS ASSOCIATION, INC.

Contents may not be reproduced in any form
without permission of the Insulated Cable Engineers Association, Inc.

All rights including translation into other
languages, reserved under the Universal Copyright Convention,
the Berne Convention for the Protection of Literary and Artistic Works,
and the International and Pan American Copyright Conventions.

INSULATED CABLE ENGINEERS ASSOCIATION, Inc.

P.O. Box 440

South Yarmouth, Massachusetts 02664 USA

FOREWORD

This Standards Publication for Concentric Neutral Cables Rated 5 to 46 kV (ICEA S-94-649) was developed by the Insulated Cable Engineers Association Inc. (ICEA).

ICEA standards are adopted in the public interest and are designed to eliminate misunderstandings between the manufacturer and the user and to assist the user in selecting and obtaining the proper product for his particular need. Existence of an ICEA standard does not in any respect preclude the manufacture or use of products not conforming to the standard. The user of this Standards Publication is cautioned to observe any health or safety regulations and rules relative to the manufacture and use of cable made in conformity with this Standard.

Requests for interpretation of this Standard must be submitted in writing to the Insulated Cable Engineering Association, Inc., P. O. Box 440, South Yarmouth, Massachusetts 02664. An official written interpretation will be provided. Suggestions for improvements gained in the use of this Standard will be welcomed by the Association.

The ICEA expresses thanks to the Association of Edison Illuminating Companies for providing the basis for some of the material included herein through their participation in the Utility Power Cable Standards Technical Advisory Committee (UPCSTAC), and to the Institute of Electrical and Electronics Engineers, Insulated Conductors Committee, Discussion Group A-14 for providing user input to this Standard.

The members of the ICEA working group contributing to the writing of this Standard consisted of the following:

F. Kuchta, Chairman

E. Bartolucci
P. Cinquemani
L. Hiivala
R. Smith
N. Ware

R. Bristol
D. Fox
F. LaGase
B. Vaughn
B. Yu

J. Cancelosi
P. Hall
A. Pack
E. Walcott

TABLE OF CONTENTS

Part 1 GENERAL	1
1.1 SCOPE	1
1.2 GENERAL INFORMATION	1
1.3 INFORMATION TO BE SUPPLIED BY PURCHASER	1
1.3.1 Characteristics of Systems on which Cable is to be Used	1
1.3.2 Quantities and Description of Cable.....	2
1.4 DEFINITIONS AND SYMBOLS	2
 Part 2 CONDUCTOR.....	5
2.0 GENERAL.....	5
2.1 PHYSICAL AND ELECTRICAL PROPERTIES.....	5
2.1.1 Copper Conductors.....	5
2.1.2 Aluminum Conductors	5
2.2 OPTIONAL SEALANT FOR STRANDED CONDUCTORS	6
2.3 CONDUCTOR SIZE UNITS.....	6
2.4 CONDUCTOR DC RESISTANCE PER UNIT LENGTH.....	6
2.4.1 Direct Measurement of dc Resistance Per Unit Length.....	6
2.4.2 Calculation of dc Resistance Per Unit Length.....	6
2.5 CONDUCTOR DIAMETER.....	7
 Part 3 CONDUCTOR SHIELD (STRESS CONTROL LAYER).....	13
3.1 MATERIAL	13
3.2 EXTRUDED SHIELD THICKNESS	13
3.2.1 Reduced Extruded Shield Thickness	13
3.3 PROTRUSIONS AND IRREGULARITIES	13
3.4 VOIDS	14
3.5 PHYSICAL REQUIREMENTS	14
3.6 ELECTRICAL REQUIREMENTS.....	14
3.6.1 Extruded Semiconducting Material	14
3.6.2 Extruded Nonconducting Material (For EPR Insulation Only)	14
3.6.3 Semiconducting Tape	14
3.7 WAFER BOIL TEST	14
 Part 4 INSULATION	15
4.1 MATERIAL	15
4.2 INSULATION THICKNESS	15
4.2.1 Selection of Proper Thickness.....	16
4.2.1.1 For Three-Phase Systems with 100 or 133 Percent Insulation Level	16
4.2.1.2 For Delta Systems Where One Phase May Be Grounded For Periods Over One Hour.....	16
4.2.1.3 For Single- and Two-Phase Systems with 100 Percent Insulation Level	16
4.2.1.4 For Single- and Two-Phase Systems with 133 Percent Insulation Level.....	16
4.3 INSULATION REQUIREMENTS	16
4.3.1 Insulation for DISCHARGE-FREE Cable Designs Only.....	16
4.3.1.1 Physical and Aging Requirements.....	16
4.3.1.2 Electrical Requirements	17
4.3.1.2.1 Partial-Discharge Extinction Level	17
4.3.1.2.2 Voltage Tests.....	17
4.3.1.2.3 Insulation Resistance Test.....	18
4.3.1.2.4 Accelerated Water Absorption	18
4.3.1.2.5 Capacity and Dissipation Factor	18

4.3.1.3	Voids, Ambers, Gels, Agglomerates and Contaminants as Applicable.....	19
4.3.1.3.1	Crosslinked Polyethylene Insulation (XLPE or TRXLPE)	19
4.3.1.3.2	Ethylene Propylene Rubber (EPR).....	19
4.3.1.4	Shrinkback - Crosslinked Polyethylene Insulation (XLPE or TRXLPE) Only.....	19
4.3.2	Insulation For DISCHARGE-RESISTANT Cable Designs Only	20
4.3.2.1	Physical and Aging Requirements.....	20
4.3.2.2	Electrical Requirements.....	21
4.3.2.2.1	Discharge (Corona) Resistance.....	21
4.3.2.2.2	Voltage Tests.....	21
4.3.2.2.3	Insulation Resistance Test.....	21
4.3.2.2.4	Accelerated Water Absorption	21
4.3.2.2.5	Capacity and Dissipation Factor	22
4.3.2.3	Voids and Contaminants.....	22
Part 5 EXTRUDED INSULATION SHIELD	25
5.1 MATERIAL	25
5.2 THICKNESS AND INDENT REQUIREMENTS	25
5.3 PROTRUSIONS	25
5.4 INSULATION SHIELD REQUIREMENTS	25
5.4.1	Insulation Shield for DISCHARGE-FREE Cable Designs Only	25
5.4.1.1	Removability	26
5.4.1.2	Voids.....	26
5.4.1.3	Physical Requirements	26
5.4.1.4	Electrical Requirements	26
5.4.1.5	Wafer Boil Test.....	26
5.4.2	Insulation Shield for DISCHARGE-RESISTANT Cable Designs Only	26
5.4.2.1	Removability.....	26
5.4.2.2	Physical Requirements	27
5.4.2.3	Electrical Requirements	27
5.4.2.4	Wafer Boil Test.....	27
Part 6 CONCENTRIC NEUTRAL CONDUCTOR	28
6.1 MATERIAL	28
6.2 CROSS-SECTIONAL AREA	28
6.3 LAY LENGTH	28
6.4 CONCENTRIC WIRES	28
6.4.1	Minimum Sizes	28
6.4.2	Contrahelical Wire	28
6.4.3	Diameter and Area.....	28
6.5 FLAT STRAPS	29
6.6 OPTIONAL WATER BLOCKING COMPONENTS FOR METALLIC SHIELD	29
Part 7 JACKETS	31
7.1 MATERIAL	31
7.1.1	Low and Linear Low Density Polyethylene, Black (LDPE/LLDPE)	31
7.1.2	Medium Density Polyethylene, Black (MDPE).....	32
7.1.3	High Density Polyethylene, Black (HDPE).....	33
7.1.4	Semiconducting Jacket Type I	34
7.1.5	Semiconducting Jacket Type II	35
7.1.6	Polyvinyl Chloride (PVC)	36
7.1.7	Chlorinated Polyethylene (CPE)	37
7.1.8	Thermoplastic Elastomer (TPE)	38
7.1.9	Polypropylene, Black (PP).....	39

7.2 JACKET TYPES	40
7.2.1 Extruded-To-Fill Jacket.....	40
7.2.2 Overlaying Jacket	40
7.3 JACKET IRREGULARITY INSPECTION.....	40
7.3.1 Non Conducting Jackets.....	40
7.3.2 Semiconducting Jackets.....	40
Part 8 CABLE ASSEMBLY AND IDENTIFICATION.....	42
8.1 MULTIPLEX CABLE ASSEMBLIES	42
8.2 CABLE IDENTIFICATION.....	42
8.2.1 Jacketed Cable	42
8.2.1.1 Optional Cable Identification	42
8.2.2 Unjacketed Cable	43
8.2.3 Optional Center Strand Identification	43
8.2.4 Optional Sequential Length Marking	43
Part 9 TESTING AND TEST METHODS.....	44
9.1 TESTING	44
9.2 SAMPLING FREQUENCY	44
9.3 CONDUCTOR TEST METHODS.....	44
9.3.1 Method for DC Resistance Determination	44
9.3.2 Cross-Sectional Area Determination.....	44
9.3.3 Diameter Determination.....	44
9.4 TEST SAMPLES AND SPECIMENS FOR PHYSICAL AND AGING TESTS.....	44
9.4.1 General	44
9.4.2 Measurement of Thickness	44
9.4.2.1 Micrometer Measurements	45
9.4.2.2 Optical Measuring Device Measurements	45
9.4.3 Number of Test Specimens	45
9.4.4 Size of Specimens	45
9.4.5 Preparation of Specimens of Insulation and Jacket.....	46
9.4.6 Specimen for Aging Test	46
9.4.7 Calculation of Area of Test Specimens	46
9.4.8 Unaged Test Procedures.....	46
9.4.8.1 Test Temperature.....	46
9.4.8.2 Type of Testing Machine.....	47
9.4.8.3 Tensile Strength Test.....	47
9.4.8.4 Elongation Test	47
9.4.9 Aging Tests	47
9.4.9.1 Aging Test Specimens	47
9.4.9.2 Air Oven Test	48
9.4.9.3 Oil Immersion Test for Polyvinyl Chloride Jacket.....	48
9.4.10 Hot Creep Test.....	48
9.4.11 Solvent Extraction.....	48
9.4.12 Wafer Boil Test for Conductor and Insulation Shields	48
9.4.12.1 Insulation Shield Hot Creep Properties	48
9.4.13 Amber, Agglomerate, Gel, Contaminant, Protrusion, Indent, Irregularity and Void Test.....	49
9.4.13.1 Sample Preparation	49
9.4.13.2 Examination.....	49
9.4.13.3 Resampling for Amber, Agglomerate, Gel, Contaminant, Protrusion, Irregularity and Void Test.....	49
9.4.13.4 Protrusion, Indentation and Irregularity Measurement Procedure	49

9.4.14 Physical Tests for Semiconducting Material Intended for Extrusion	50
9.4.14.1 Test Sample	50
9.4.14.2 Test Specimens	50
9.4.14.3 Elongation	51
9.4.15 Retests for Physical and Aging Properties and Thickness.....	51
9.5 DIMENSIONAL MEASUREMENTS OF THE METALLIC SHIELD	51
9.6 DIAMETER MEASUREMENT OF INSULATION AND INSULATION SHIELD	51
9.7 TESTS FOR JACKETS	51
9.7.1 Heat Shock	51
9.7.2 Heat Distortion	52
9.7.3 Cold Bend	52
9.8 VOLUME RESISTIVITY	52
9.8.1 Conductor Shield (Stress Control)	52
9.8.2 Insulation Shield.....	53
9.8.3 Semiconducting Jacket Radial Resistivity Test	53
9.8.3.1 Sample Preparation	53
9.8.3.2 Test Equipment Setup	54
9.8.3.3 Calculation.....	55
9.9 ADHESION (Insulation Shield Removability) TEST	56
9.10 SHRINKBACK TEST PROCEDURE	56
9.10.1 Sample Preparation	56
9.10.2 Test Procedure	56
9.10.3 Pass/Fail Criteria and Procedure	56
9.11 RETESTS ON SAMPLES	56
9.12 VOLTAGE TESTS	57
9.12.1 General	57
9.12.2 AC Voltage Test.....	57
9.13 PARTIAL-DISCHARGE TEST PROCEDURE	57
9.14 METHOD FOR DETERMINING DIELECTRIC CONSTANT AND DIELECTRIC STRENGTH OF EXTRUDED NONCONDUCTING POLYMERIC STRESS CONTROL LAYERS	57
9.15 MOISTURE CONTENT	57
9.15.1 Moisture Under the Jacket.....	57
9.15.2 Moisture in the Conductor	57
9.15.3 Water Expulsion Procedure.....	58
9.15.4 Presence of Water Test.....	58
9.16 PRODUCTION TEST SAMPLING PLANS	59
 Part 10 QUALIFICATION TESTS	 62
10.0 GENERAL	62
10.1 CORE MATERIAL QUALIFICATION TESTS	62
10.1.1 Conductor Shield/Insulation Qualification	62
10.1.2 Insulation Shield Qualification	63
10.1.3 High Voltage Time Test (HVTT) Procedure.....	65
10.1.4 Hot Impulse Test Procedure.....	65
10.1.5 Cyclic Aging	65
10.1.5.1 Cable Length	66
10.1.5.2 Sample Preparation	66
10.1.5.3 Conduit	66
10.1.5.4 Load Cycle	66
10.1.6 Accelerated Water Treeing Test (AWTT) Procedure	66
10.1.6.1 General	66
10.1.6.2 Sample Preparation	66

10.1.6.3	Aging Time	66
10.1.6.4	Test Procedure.....	67
10.1.6.5	Water pH	67
10.1.7	Qualification Test Electrical Measurements.....	68
10.1.8	Qualification Test Physical Measurements.....	68
10.2	THERMOMECHANICAL QUALIFICATION TEST - Optional	68
10.2.1	Scope.....	68
10.2.2	Procedure	68
10.2.2.1	Fixture.....	68
10.2.2.2	Load Cycling.....	68
10.2.2.3	Electrical Measurements	69
10.2.2.4	Physical Measurements Before and After the Thermomechanical Design Test	69
10.3	JACKET MATERIAL QUALIFICATION TESTS	70
10.3.1	Polyethylene Jackets	70
10.3.1.1	Environmental Stress Cracking Test	70
10.3.1.1.1	Test Specimen	71
10.3.1.1.2	Test Procedure.....	71
10.3.1.2	Absorption Coefficient Test.....	71
10.3.2	Semiconducting Jackets.....	71
10.3.2.1	Brittleness Test	71
10.3.3	Polyvinyl Chloride and Chlorinated Polyethylene Jackets.....	71
10.3.3.1	Sunlight Resistance	71
10.3.3.1.1	Test Samples	71
10.3.3.1.2	Test Procedure.....	71
10.4	CV EXTRUSION QUALIFICATION TEST	71
10.4.1	Thermal Conditioning.....	72
10.4.2	Dissipation Factor Verification.....	72
10.4.3	AC Withstand Verification.....	72
10.5	OTHER QUALIFICATION TESTS	72
10.5.1	Insulation Resistance.....	72
10.5.2	Accelerated Water Absorption Tests	73
10.5.3	Resistance Stability Test	73
10.5.4	Brittleness Test for Semiconducting Shields	73
10.5.4.1	Test Samples	73
10.5.4.2	Test Procedure.....	73
10.5.5	Dry Electrical Test for EPR Class III Insulation Only	73
10.5.5.1	Test Samples	73
10.5.5.2	Test Procedure.....	73
10.5.5.3	Electrical Measurements	73
10.5.6	Discharge Resistance Test for EPR Class IV Insulation Only	73
10.5.6.1	Test Specimens	74
10.5.6.2	Test Environment	74
10.5.6.3	Test Electrodes	74
10.5.7	Dissipation Factor Characterization Test	74
10.5.7.1	Test Samples	74
10.5.7.2	Thermal Conditioning	74
10.5.7.3	Dissipation Factor Testing	75
Part 11	APPENDICES	76
APPENDIX A	NEMA, ICEA, IEEE, ASTM AND ANSI STANDARDS	76
A1	NEMA PUBLICATIONS	76
A2	ICEA PUBLICATIONS.....	76

A3	IEEE STANDARDS	76
A4	ASTM STANDARDS	76
A5	ANSI STANDARDS	78
APPENDIX B	EMERGENCY OVERLOADS	79
APPENDIX C	PROCEDURE FOR DETERMINING DIAMETERS OF CABLE	80
APPENDIX D	SHIELDING.....	85
D1	DEFINITION OF SHIELDING	85
D2	FUNCTIONS OF SHIELDING.....	85
D3	USE OF INSULATION SHIELDING	85
D4	GROUNDING OF THE INSULATION SHIELD	86
D5	SHIELD MATERIALS	86
D6	SPlices AND TERMINATIONS	86
APPENDIX E	HANDLING AND INSTALLATION PARAMETERS	87
E1	INSTALLATION TEMPERATURES	87
E2	RECOMMENDED MINIMUM BENDING RADIUS.....	87
E3	DRUM DIAMETERS OF REELS	87
E4	MAXIMUM TENSION AND SIDEWALL BEARING PRESSURES.....	87
E5	TESTS DURING AND AFTER INSTALLATION	87
E5.1	During Installation	87
E5.2	After Installation.....	87
E5.3	In Service	87
APPENDIX F	OPTIONAL FACTORY DC TEST	89
APPENDIX G	REDUCED NEUTRAL DESIGNS	90
APPENDIX H	ADDITIONAL CONDUCTOR INFORMATION.....	94
APPENDIX I	ETHYLENE ALKENE COPOLYMER (EAM)	97

LIST OF TABLES

Table 2-1	Weight Increment Factors	7
Table 2-2	Schedule for Establishing Maximum Direct Current Resistance Per Unit Length of Completed Cable Conductors listed in Table 2-4.....	7
Table 2-3	Nominal Direct Current Resistance in Ohms Per 1000 Feet at 25 °C of Solid and Concentric Lay Stranded Conductor.....	8
Table 2-3 (Metric)	Nominal Direct Current Resistance in Milliohms Per Meter at 25 °C of Solid and Concentric Lay Stranded Conductor.....	9
Table 2-4	Nominal Diameters for Copper and Aluminum Conductors.....	10
Table 2-4 (Metric)	Nominal Diameters for Copper and Aluminum Conductors.....	11
Table 2-5	Factors for Determining Nominal Resistance of Stranded Conductors Per 1000 Feet at 25 °C	12
Table 3-1	Extruded Conductor Shield Thickness	13
Table 3-2	Extruded Conductor Shield Requirements	14
Table 4-1	Conductor Maximum Temperatures	15
Table 4-2	Insulation Physical Requirements Discharge-Free Designs	17
Table 4-3	Accelerated Water Absorption Properties Discharge-Free Designs	18
Table 4-4	Dielectric Constant and Dissipation Factor Discharge-Free Designs	18
Table 4-5	Shrinkback Test Requirements Cables Having Sealed Strand Conductors and/or a Tape Over the Conductor	19
Table 4-6	Shrinkback Test Requirements All Cables Not Covered by Table 4-5	20
Table 4-7	Insulation Physical Requirements Discharge-Resistant Designs	20
Table 4-8	Accelerated Water Absorption Properties Discharge-Resistant Designs	21
Table 4-9	Dielectric Constant and Dissipation Factor Discharge-Resistant Designs	22
Table 4-10	BIL Values	22
Table 4-11	Conductor Sizes, Insulation Thicknesses and Test Voltages	23

Table 4-11 (Metric)	Conductor Sizes, Insulation Thicknesses and Test Voltages	23
Table 5-1	Insulation Shield Thickness Cables Without Embedded Corrugated Wires	25
Table 5-2	Extruded Insulation Shield Requirements Discharge-Free Designs	26
Table 5-3	Extruded Insulation Shield Requirements Discharge-Resistant Designs	27
Table 6-1	Concentric Neutral Wire Size	29
Table 6-2	Full Neutral Concentric Copper Conductor	29
Table 6-3	One-third Neutral Concentric Copper Conductor	30
Table 7-1	Low Density and Linear Low Density Polyethylene, Black (LDPE/LLDPE)	31
Table 7-2	Medium Density Polyethylene, Black (MDPE)	32
Table 7-3	High Density Polyethylene, Black (HDPE)	33
Table 7-4	Semiconducting Jacket Type I	34
Table 7-5	Semiconducting Jacket Type II	35
Table 7-6	Polyvinyl Chloride (PVC)	36
Table 7-7	Chlorinated Polyethylene (CPE)	37
Table 7-8	Thermoplastic Elastomer (TPE)	38
Table 7-9	Polypropylene, Black (PP)	39
Table 7-10	Extruded-To-Fill Jacket Thickness and Test Voltage	41
Table 7-11	Overlaying Jacket Thickness and Test Voltage	41
Table 8-1	Nominal Insulation Thickness	43
Table 9-1	Test Specimens for Physical and Aging Tests	45
Table 9-2	Insulation Shield Hot Creep Requirements	49
Table 9-3	Bending Requirements for Heat Shock Test	52
Table 9-4	Bending Requirements for Cold Bend Test	52
Table 9-5	Summary of Production Tests and Sampling Frequency Requirements	59
Table 9-6	Plan E	61
Table 9-7	Plan F	61
Table 10-1	Maximum Temperature Gradient for Thermal Aging	69
Table 10-2	Generic Grouping of Cable Components	70
Table 10-3	AC Withstand Voltage Requirements 15-35 kV Rated Cables	72
Table C-1	Insulation Diameter Calculation	80
Table C-2	Insulation Shield Adders	81
Table C-3	Calculated Dimensions – Concentric Stranding	82
Table C-4	Calculated Dimensions – Compressed Stranding	83
Table C-5	Calculated Dimensions – Compact Stranding	84
Table E-1	DC Field Test Voltages	88
Table F-1	DC Test Voltages	89
Table G-1	One-sixth Neutral Concentric Conductor for Copper Center Conductor	90
Table G-2	One-eighth Neutral Concentric Conductor for Copper Center Conductor	90
Table G-3	One-twelfth Neutral Concentric Conductor for Copper Center Conductor	91
Table G-4	One-sixth Neutral Concentric Conductor for Aluminum Center Conductor	91
Table G-5	One-eighth Neutral Concentric Conductor for Aluminum Center Conductor	92
Table G-6	One-twelfth Neutral Concentric Conductor for Aluminum Center Conductor	92
Table H-1	Solid Aluminum and Copper Conductors	94
Table H-2	Concentric Stranded Class B Aluminum and Copper Conductors	95
Table H-3	Concentric Stranded Class C and D Aluminum and Copper Conductors	96