
Road vehicles — Unified diagnostic services (UDS) —

**Part 3:
Unified diagnostic services on CAN
implementation (UDSonCAN)**

Véhicules routiers — Services de diagnostic unifiés (SDU) —

Partie 3: SDU sur l'implémentation du gestionnaire de réseau de communication (SDU sur CAN)





COPYRIGHT PROTECTED DOCUMENT

© ISO 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols and abbreviated terms	1
4.1 Symbols	1
4.2 Abbreviated terms	2
5 Conventions	2
6 Service primitive interface definition	3
7 Technical requirements overview	3
8 Application layer	4
8.1 ISO 14229-1 service primitive parameters	4
8.2 A_Data.req, A_Data.ind, and A_Data.conf service interface	4
8.3 UDSONCAN services overview	4
8.4 A_PDU definition	5
8.5 ReadDataByPeriodicIdentifier service UDSONCAN implementation requirements	6
8.5.1 UUDT periodic transmission response message handling	6
8.5.2 Service interface – UUDT	6
8.5.3 UUDT service primitive parameters	8
8.5.4 UUDT message format	9
8.5.5 Periodic transmission message flow	10
8.6 Timing parameter definition	13
8.6.1 Request and response message timing parameter values	13
8.6.2 Unsolicited response messages	13
9 Presentation layer	13
10 Session layer	13
10.1 Service primitive parameter definition	13
10.2 S_Data.req, S_Data.ind, and S_Data.conf service interface	13
11 Transport layer	14
11.1 USDT service primitive parameters	14
11.2 T_Data.req, T_Data.ind, and T_Data.conf service interface	14
11.3 Transport protocol	14
11.4 T_PDU definition	14
11.5 DoCAN transport and network layer interface adaptation	14
11.5.1 Mapping of data link independent service primitives onto CAN data link-dependent service primitives	14
11.5.2 Mapping of T_PDU onto N_PDU	15
12 Network layer	15
12.1 Service primitive parameter definition	15
12.2 N_Data.req, N_Data.ind, and N_Data.conf service interface	15
12.3 Network layer services	16
12.4 N_PDU definition	16
12.5 N_TAType service primitive parameter	16
12.6 Same N_TAType request and associated response message format	16
13 Data link layer	17
13.1 Service primitive parameter definition	17
13.2 L_Data.req, L_Data.ind, and L_Data.conf service interface	17
13.3 Usage of ISO 15765-4-defined 11-bit CAN identifiers for enhanced diagnostics	17

13.4 Usage of ISO 15765-4-defined 29-bit CAN identifiers for enhanced diagnostics..... 18

14 Physical layer..... 18

Bibliography 19