INTERNATIONAL STANDARD

ISO 20457

First edition 2018-09

Plastics moulded parts — Tolerances and acceptance conditions

Moulages plastiques — Tolérances et conditions de réception



ISO 20457:2018(E)



COPYRIGHT PROTECTED DOCUMENT

© ISO 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Fax: +41 22 749 09 47 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Contents		Page
Forev	word	iv
Intro	duction	v
1	Scope	
2	Normative references	
3	Terms and definitions	
4	Symbols and abbreviated terms	
•	4.1 General	
	4.2 Symbols	
	4.3 Abbreviated terms	
5	Tolerancing of plastic moulded parts	
	5.1 General 5.2 Intention	
	5.3 General tolerances	
	5.4 Direct tolerancing (individual tolerancing)	5
	5.5 Tolerancing of draft angles	
	5.6 Dimensioning, tolerancing and measuring of radii5.7 Specification of freeform surfaces	
_		
6	Moulding compound properties 6.1 General	
	6.2 Moulding shrinkage and shrinkage anisotropies	
	6.3 Moulded material stiffness or hardness	
7	Dimensional and geometrical tolerancing	8
	7.1 Dimensional tolerancing	8
	7.1.1 Tolerance grades for features of sizes	
	7.1.2 Determination of the tolerance grades7.2 Geometrical tolerancing	
	7.3 Parting line/Tool offset	
	7.4 Tolerancing of angular dimensions	17
8	Acceptance conditions for moulded part production (ABF)	17
Anne	ex A (informative) Dimensional reference levels for application and production of the moulded parts	1Ω
Anne	ex B (informative) Causes and influential factors on the moulding shrinkage of non-	
_	porous plastics	
	ex C (informative) Evaluation of the production expense	
	ex D (informative) Validation of machine or process capability	24
Anne	x E (informative) Main causes for dimension, form and location deviations in moulded part production	25
Anne	ex F (informative) Example for determining the $D_{\rm P}$ dimension for application of Table 9	26
Anne	ex G (informative) Feasible acceptance parameters	27
Rihli	ngranhy	28

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 61, *Plastics*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

In comparison to metal materials, significantly larger deviations with respect to dimension, form and location are expected when manufacturing moulded parts. Based on particular properties, such as high deformability and low stiffness, the functional accuracy requirements in order to economically manufacture moulded parts are much lower for plastics than for metals.

The physical and chemical properties as well as the material modification options of plastics are vastly different from those of metals. Properties of plastics relevant to dimensional accuracy in the moulding application and during processing by the original mould method (injection moulding, compression moulding, rotational moulding) require a different evaluation and quantification of geometrical tolerances in comparison to metal materials. The tolerance standards applicable for metal parts, therefore, cannot be adopted for plastic structures or can only be applied to a very limited extent which led to the development of this document.

The unique properties of plastics mean that three different dimensional reference levels defined in Annex A and characterized in respect to the main influential factors are taken into consideration.

The following is the preferred sequence of steps to ensure effective cooperation in the effective design and development of moulded parts.

- a) The part designer specifies the functionally required tolerances based on the application requirements including, part functionality, use environment, and any assembly requirements.
- b) The moulded part manufacturer confirms that the functionally required tolerance is greater than or equal to the tolerance capability of the manufacturing technology to be used. This is to avoid impractical tolerances which cannot be achieved without incurring adverse economic or productivity effects. The functionally required tolerances should always be defined in the design documentation.
- c) The functionally required tolerances should always be defined in the design documentation in order to establish the basis for determining the moulding shrinkage. This is to prevent situations in which the functionally required tolerances cannot be achieved, if at all, without excessive scrap generation and excessive cost. After order placement, calculated values with respect to the moulding shrinkage should be agreed between the part manufacturer and toolmaker or tool designer, with consultation with the material supplier as necessary.

Dimensional control of the moulded part is primarily affected by the material specified, the part design and tool layout, and the processing conditions.

In addition to the factors affecting dimensional control, there are other factors which influence dimensions, part integrity and mechanical properties. These factors include anisotropic behaviour, warpage and distortion due to non-uniform thicknesses and resulting non-uniform cooling rates, and fill profiles. These factors and the basic complexity of polymer systems make standardization much more difficult in comparison to conventional materials such as metals.

Because of the unavoidable process-induced factors, deviations are therefore expected in the moulded part. The procedure in case of deviations depends on the function of the moulded part and is subject to mandatory contractual agreement.

- eliminate deviation by design measures (strengthening ribs, optimized material thickness, optimized fill profiles, etc.);
- correct deviation by specified retention in the tool, i.e. extended cooling cycles;
- acceptance of non-conformance.