
**Tractors and machinery for agriculture
and forestry — Serial control and
communications data network —**

**Part 2:
Physical layer**

*Tracteurs et matériels agricoles et forestiers — Réseaux de commande
et de communication de données en série —*

Partie 2: Couche physique



Reference number
ISO 11783-2:2012(E)



COPYRIGHT PROTECTED DOCUMENT

© ISO 2012

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 General description	1
4.1 Network physical layer	1
4.2 Physical media	1
4.3 Differential voltage	2
4.4 Bus	2
4.4.1 Levels	2
4.4.2 Voltage range	2
4.4.3 Termination	2
4.5 Resistance and capacitance	3
4.5.1 Internal resistance (R_{in}), capacitance (C_{in})	3
4.5.2 Differential internal resistance (R_{diff}), capacitance (C_{diff})	4
4.6 Bit time	5
4.7 AC parameters	5
5 Functional description	6
6 Electrical specifications	7
6.1 Electrical data	7
6.1.1 General	7
6.1.2 Absolute maximum ratings	7
6.1.3 DC parameters	7
6.1.4 Bus voltages (operational)	9
6.1.5 Electrostatic discharge (ESD)	9
6.2 Physical media parameters	9
6.2.1 Twisted quad cable	9
6.2.2 Topology	10
6.2.3 ECU connection to TBC_PWR and TBC_RTN	11
6.2.4 Power For TBC_PWR and TBC_RTN	11
6.3 TBC parameters	12
6.4 Connectors	13
6.4.1 General	13
6.4.2 Bus extension connector	14
6.4.3 Implement bus breakaway connector	16
6.4.4 In-cab connector	21
6.4.5 Diagnostic connector	24
7 Conformance tests	29
7.1 General requirements	29
7.2 Internal resistance	29
7.3 Internal differential resistance	30
7.4 ECU recessive input threshold	30
7.5 ECU dominant input threshold	31
7.6 ECU dominant output	31
7.7 ECU internal delay time	32
8 Bus failure and fault confinement	33
8.1 General	33

8.2 Loss of network connection33

8.3 Node power or ground loss33

8.4 Open and short failures33

Annex A (informative) Protocol controller timing and naming.....37

Annex B (informative) Examples of physical layer circuits41

Bibliography50

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

ISO 11783-2 was prepared by Technical Committee ISO/TC 23, *Tractors and machinery for agriculture and forestry*, Subcommittee SC 19, *Agricultural electronics*.

This second edition cancels and replaces the first edition (ISO 11783-2:2002), which has been technically revised. It also incorporates the Amendment ISO 11783-2:2002/Amd.1:2006 and the Technical Corrigendum ISO 11783-2:2002/Cor.1:2003.

ISO 11783 consists of the following parts, under the general title *Tractors and machinery for agriculture and forestry — Serial control and communications data network*:

- *Part 1: General standard for mobile data communication*
- *Part 2: Physical layer*
- *Part 3: Data link layer*
- *Part 4: Network layer*
- *Part 5: Network management*
- *Part 6: Virtual terminal*
- *Part 7: Implement messages application layer*
- *Part 8: Power train messages*
- *Part 9: Tractor ECU*
- *Part 10: Task controller and management information system data interchange*
- *Part 11: Mobile data element dictionary*
- *Part 12: Diagnostics services*
- *Part 13: File server*
- *Part 14: Sequence control*

Introduction

Parts 1 to 14 of ISO 11783 specify a communications system for agricultural equipment based on ISO 11898-1^[4] and ISO 11898-2^[5]. SAE J1939^[8] documents, on which parts of ISO 11783 are based, were developed jointly for use in truck and bus applications and for construction and agriculture applications. Joint documents were completed to allow electronic units that meet the truck and bus SAE J1939 specifications to be used by agricultural and forestry equipment with minimal changes. General information on ISO 11783 is to be found in ISO 11783-1.

The purpose of ISO 11783 is to provide an open, interconnected system for on-board electronic systems. It is intended to enable electronic control units (ECUs) to communicate with each other, providing a standardized system.

The International Organization for Standardization (ISO) draws attention to the fact that it is claimed that compliance with this part of ISO 11783 may involve the use of a patent concerning the controller area network (CAN) protocol referred to throughout the document.

ISO takes no position concerning the evidence, validity and scope of this patent.

The holder of this patent has assured ISO that he is willing to negotiate licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holder of this patent right is registered with ISO. Information may be obtained from:

Robert Bosch GmbH
Wernerstrasse 51
Postfach 30 02 20
D-70442 Stuttgart-Feuerbach
Germany

Attention is drawn to the possibility that some of the elements of this part of ISO 11783 may be the subject of patent rights other than those identified above. ISO shall not be held responsible for identifying any or all such patent rights.

Tractors and machinery for agriculture and forestry — Serial control and communications data network —

Part 2: Physical layer

1 Scope

ISO 11783 as a whole specifies a serial data network for control and communications on forestry or agricultural tractors and mounted, semi-mounted, towed or self-propelled implements. Its purpose is to standardize the method and format of transfer of data between sensors, actuators, control elements and information storage and display units, whether mounted on, or part of, the tractor or implement, and to provide an open interconnect system for electronic systems used by agricultural and forestry equipment. This part of ISO 11783 defines and describes the network's 250 kbit/s, twisted, non-shielded, quad-cable physical layer.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1724, *Road vehicles — Connectors for the electrical connection of towing and towed vehicles — 7-pole connector type 12 N (normal) for vehicles with 12 V nominal supply voltage*

ISO 11783-1, *Tractors and machinery for agriculture and forestry — Serial control and communications data network — Part 1: General standard for mobile data communication*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 11783-1 apply.

4 General description

4.1 Network physical layer

The physical layer of a network is the realization of the electrical connection of a number of electronic control units (ECUs) to a bus segment of the network. The total number of ECUs connected is limited by the electrical loads on the bus segment. In accordance with the electrical parameters specified by this part of ISO 11783, the limit shall be 30 ECUs per segment.

4.2 Physical media

This part of ISO 11783 defines a physical media of twisted quad cable. Two of the conductors, designated CAN_H and CAN_L, are driven with the communications signals. The names of the ECU pins corresponding to these conductors are also designated CAN_H and CAN_L. The third and fourth conductors, designated TBC_PWR and TBC_RTN, provide power for the terminating bias circuits (TBCs) on the bus segments.