

Second edition
2011-06-01

AMENDMENT 4
2013-12-01

Graphical symbols — Safety colours and safety signs — Registered safety signs

AMENDMENT 4

*Symboles graphiques — Couleurs de sécurité et signaux de sécurité —
Signaux de sécurité enregistrés*

AMENDEMENT 4



Reference number
ISO 7010:2011/Amd.4:2013(E)



COPYRIGHT PROTECTED DOCUMENT

© ISO 2013

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT), see the following URL: Foreword - Supplementary information

The committee responsible for this document is ISO/TC 145, *Graphical symbols*, Subcommittee SC 2, *Safety identification, signs, shapes, symbols and colours*.

Graphical symbols — Safety colours and safety signs — Registered safety signs

AMENDMENT 4


IMPORTANT — The colours represented in the electronic file of this International Standard can be neither viewed on screen nor printed as true representations. Although the copies of this International Standard printed by ISO have been produced to correspond (with an acceptable tolerance as judged by the naked eye) to the requirements of ISO 3864-4, it is not intended that these printed copies be used for colour matching. Instead consult ISO 3864-4 which provides colourimetric and photometric properties together with, as a guideline, references from colour order systems.

Add the following safety signs:

- E024: Evacuation temporary refuge
- E027: Medical grab bag
- E028: Oxygen resuscitator
- E029: Emergency escape breathing device
- E031: Shipboard general alarm
- E032: Shipboard assembly station
- E033: Door slides right to open
- E034: Door slides left to open
- E036: Lifeboat
- E037: Rescue boat
- E038: Liferaft
- E039: Davit-launched liferaft
- E040: Lifebuoy
- E041: Lifebuoy with line
- E042: Lifebuoy with light
- E043: Lifebuoy with line and light
- E044: Lifejacket
- E045: Child's lifejacket
- E046: Infant's lifejacket
- E047: Search and rescue transponder
- E048: Survival craft distress signals
- E049: Rocket parachute flare

- E050: Line-throwing appliance
- E051: Two-way VHF radiotelephone apparatus
- E052: Emergency position indicating radio beacon
- E053: Embarkation ladder
- E054: Marine evacuation slide
- E055: Marine evacuation chute
- E056: Survival clothing
- E057: Door opens by pulling on the left-hand side
- E058: Door opens by pulling on the right-hand side
- F008: Fixed fire extinguishing battery
- F009: Wheeled fire extinguisher
- F010: Portable foam applicator unit
- F011: Water fog applicator
- F012: Fixed fire extinguishing installation
- F013: Fixed fire extinguishing bottle
- F014: Remote release station
- F015: Fire monitor
- M037: Close and secure hatches in launch sequence
- M038: Start engine in launch sequence
- M039: Lower lifeboat to the water in launch sequence
- M040: Lower liferaft to the water in launch sequence
- M041: Lower rescue boat to the water in launch sequence
- M042: Release falls in launch sequence
- M043: Start water spray in launch sequence
- M044: Start air supply in launch sequence
- M045: Release lifeboat gripes in launch sequence

Safety sign E024: Evacuation temporary refuge

	Reference No. ISO 7010-E024
	Referent Evacuation temporary refuge
	Function To indicate the location of a temporary safe area (refuge) to await rescue assistance, provided for those unable to use stairs in the event of an emergency evacuation
	Image content Human figure in wheelchair (profile), four white arrows coming from the corners pointing to it
<p>Hazard</p> <p>Not being able to locate an area provided for temporary waiting for rescue assistance for those unable to use stairs in the event of an emergency evacuation</p> <p>Human behaviour that is intended to be caused after understanding the safety sign's meaning</p> <p>Being aware of the location of an area provided for temporary waiting for rescue assistance for those unable to use stairs in the event of an emergency evacuation</p> <p>Related referents</p> <p>—</p> <p>Additional information</p> <p>Test data obtained according to ISO 9186-1:2007 are not available from more than one country. Findings from national testing, however, showed that in one country the safety sign did not reach the criteria of acceptability. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.</p>	