

Translated and Published by Japanese Standards Association

JIS K 6259-2:2015 (JRMA/JSA) Rubber, vulcanized or thermoplastic—Determination of ozone resistance—Part 2: Determination of the ozone concentration

ICS 83.060 Reference number : JIS K 6259-2 : 2015 (E)

This is a preview. Click here to purchase the full publication.

Date of Establishment: 2015-09-24 Date of Public Notice in Official Gazette: 2015-09-24 Investigated by: Japanese Industrial Standards Committee Standards Board for ISO area Technical Committee on Chemical Products and Analytical Methods

JIS K 6259-2:2015, First English edition published in 2016-08

Translated and published by: Japanese Standards Association Mita MT Building, 3-13-12, Mita, Minato-ku, Tokyo, 108-0073 JAPAN

> In the event of any doubts arising as to the contents, the original JIS is to be the final authority.

© JSA 2016

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan

NH/AT

This is a preview. Click here to purchase the full publication.

Contents

Page

Introduction1	
1	Scope1
2	Normative references1
3	Principle2
4	Ozone concentration measurement device2
5	Calibration3
6 6.1 6.2 6.3	Measuring method ····································
7	Expression of results
8	Test report5
Ann	ex A (informative) The relation between the partial pressure of ozone and concentration
Annex B (normative) Measuring method B (Instrumental method)7	
Annex C (normative) Measuring method C (Wet chemical method) $\cdots \cdots \cdots 10$	
Annex JA (normative) Calibration of ultraviolet absorption photometer21	
Ann	ex JB (informative) Comparison table between JIS and corresponding International Standard25

K 6259-2 : 2015

Foreword

This translation has been made based on the original Japanese Industrial Standard established by the Minister of Economy, Trade and Industry through deliberations at the Japanese Industrial Standards Committee according to the proposal for establishment of Japanese Industrial Standard submitted by The Japan Rubber Manufacturers Association (JRMA)/Japanese Standards Association (JSA) with the draft being attached, based on the provision of Article 12 Clause 1 of the Industrial Standardization Law.

This **JIS** document is protected by the Copyright Law.

Attention is drawn to the possibility that some parts of this Standard may conflict with patent rights, applications for a patent after opening to the public or utility model rights. The relevant Minister and the Japanese Industrial Standards Committee are not responsible for identifying any of such patent rights, applications for a patent after opening to the public or utility model rights.

JIS K 6259 series consists of the following 2 parts under the general title "*Rubber*, vulcanized or thermoplastic—Determination of ozone resistance":

Part 1: Static and dynamic strain testing Part 2: Determination of the ozone concentration

This is a preview. Click here to purchase the full publication.

Rubber, vulcanized or thermoplastic— Determination of ozone resistance— Part 2: Determination of the ozone concentration

Introduction

This Japanese Industrial Standard has been prepared based on the first edition of **ISO 1431-3** published in 2000 with some modifications of the technical contents.

The portions given sidelines or dotted underlines are the matters in which the contents of the corresponding International Standard have been modified. A list of modifications with the explanations is given in Annex JB.

1 Scope

This Standard specifies the methods for the determination of ozone concentration in test chamber.

Moreover, this Standard is applied to three types of method such as the ultraviolet absorption method (Measuring method A), the instrumental method (Measuring method B) and the wet chemical method (Measuring method C). However, the ultraviolet absorption method is the reference method for the calibration of ozone concentration and used for the calibration of the instrumental method and the wet chemical method.

NOTE : The International Standard corresponding to this Standard and the symbol of degree of correspondence are as follows.

ISO 1431-3:2000 Rubber, vulcanized or thermoplastic—Resistance to ozone cracking—Part 3: Reference and alternative methods for determining the ozone concentration in laboratory test chambers (MOD)

In addition, symbols which denote the degree of correspondence in the contents between the relevant International Standard and **JIS** are IDT (identical), MOD (modified), and NEQ (not equivalent) according to **ISO/IEC Guide 21-1**.

WARNING Persons using this Standard should be familiar with normal laboratory practice. This Standard does not purport to address all of the safety problems, if any, associated with its use. It is the responsibility of the user of this Standard to establish appropriate safety and health practices.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this Standard. The most recent editions of the standards (including amendments) indicated below shall be applied.

JIS K 6259-1 Rubber, vulcanized or thermoplastic—Determination of ozone resistance—Part 1: Static and dynamic strain testing