

Standard Marking System for Valves, Fittings, Flanges, and Unions

Standard Practice
Developed and Approved by the
Manufacturers Standardization Society of the
Valve and Fittings Industry, Inc.
127 Park Street, NE

Vienna, Virginia 22180-4602 Phone: (703) 281-6613

Fax: (703) 281-6671

E-mail: standards@msshq.org



www.msshq.org

This MSS Standard Practice was developed under the consensus of the MSS Technical Committee 302 and the MSS Coordinating Committee. In addition, this Standard Practice was approved by an ANSI/MSS Consensus Committee and ANSI as a revised American National Standard. The content of this Standard Practice is the resulting efforts of competent and experienced volunteers to provide an effective, clear, and non-exclusive standard that will benefit the industry as a whole. This MSS Standard Practice describes minimal requirements and is intended as a basis for common practice by the manufacturer, the user, and the general public. The existence of an MSS Standard Practice does not in itself preclude the manufacture, sale, or use of products not conforming to the Standard Practice. Mandatory conformance to this Standard Practice is established only by reference in other documents such as a code, specification, sales contract, or public law, as applicable. MSS has no power, nor does it undertake, to enforce or certify compliance with this document. Any certification or other statement of compliance with the requirements of this Standard Practice shall not be attributable to MSS and is solely the responsibility of the certifier or maker of the statement.

"Unless indicated otherwise within this MSS Standard Practice, other standards documents referenced to herein are identified by the date of issue that was applicable to this Standard Practice at the date of approval of this MSS Standard Practice (see Annex C). This Standard Practice shall remain silent on the validity of those other standards of prior or subsequent dates of issue even though applicable provisions may not have changed."

By publication of this Standard Practice, no position is taken with respect to the validity of any potential claim(s) or of any patent rights in connection therewith. MSS shall not be held responsible for identifying any patent rights. Users are expressly advised that determination of patent rights and the risk of infringement of such rights are entirely their responsibility.

For all MSS Standard Practices, the term "shall" means "must" and "shall not" means "must not".

In this Standard Practice, all text, notes, annexes, tables, figures, and references are construed to be essential to the understanding of the message of the standard, and are considered normative, unless denoted as "supplemental". All appendices, if included, that appear in this document are construed as "supplemental". Supplemental information, within this Standard Practice, does not include mandatory or normative requirements.

U.S. customary units in this Standard Practice are the standard; the SI (metric) units are for reference only.

This Standard Practice has been substantively revised from the previous 2013 edition. It is suggested that if the user is interested in knowing what changes have been made, that a direct page by page comparison should be made of this document and that of the previous edition.

Non-toleranced dimensions in this Standard Practice are nominal unless otherwise specified. For the purposes of this Standard Practice, the term "shall" means "must" and "shall not" means "must not".

Excerpts of this Standard Practice may be quoted with permission. Credit lines should read 'Extracted from ANSI/MSS SP-25-2018 with permission of the publisher, Manufacturers Standardization Society of the Valve and Fittings Industry'. Reproduction and/or electronic transmission or dissemination is prohibited under copyright convention unless written permission is granted by the Manufacturers Standardization Society of the Valve and Fittings Industry Inc. All rights reserved.

Originally Approved: July 1934 Originally Published: July 1935

Current Edition Approved by MSS: July 2017 Current Edition Approved by ANSI: March 2018 Current Edition Published: September 2018

MSS is a registered trademark of Manufacturers Standardization Society of the Valve and Fittings Industry, Inc.

Copyright ©, 2018 by Manufacturers Standardization Society of the Valve and Fittings Industry, Inc.

Printed in U.S.A.

FOREWORD

The original publication of the Standard Marking System was developed by MSS in 1934. It stated the basic rules but was considered to need more details for general use. A second edition was therefore prepared with additional details and examples and was published in 1936.

The third edition, published in 1954, recognized the use of new materials, increased operating temperatures and pressures, and added more examples of markings for regular products.

In 1958, the fourth edition incorporated relatively minor changes and updates; including some additional marking examples.

For the fifth edition, published in 1960, the format was revised to permit the use of nameplates on valve bodies. In addition, this version added requirements for the marking of ductile iron products.

The sixth edition, published in 1964, broadened the scope of this marking standard and revised the examples and sections of the text to reflect changes in piping requirements.

The seventh edition, published in 1978, was substantially revised and re-written to simplify its cross references and to improve readability. This edition incorporated the marking features of pressure-temperature marking designations contained in existing American National Standards involving products and materials. It was also rearranged so that the General Rules were stated in Sections 1 through 11 and amplified in Sections 12 through 18; which gave specific rules and examples of marking requirements relating to various products and materials.

In 1993, the eighth edition incorporated relatively minor changes and updates; including minor revisions required to harmonize this document with then-current MSS Standard Practices.

The tenth edition, published in 2008, included revisions to ASME B16.34 example markings and mandatory MSS conformance markings, in addition to clarifications of other general requirements.

The eleventh edition, published in 2013, included new Annexes for Reference Tables and Marking Requirement Examples, the addition of laser marking techniques and country of origin marking, substantial revision and re-formatting to update the document text and tables, and other revisions to provide clarification as warranted. The 2013 edition was also approved as an American National Standard.

With this twelfth edition, published in 2018, SP-25 observes over 83 years of providing the industry with standardized marking guidance. This twelfth edition includes a new section involving products with rating designations which are constant throughout a specified temperature range; revised requirements involving the marking of a manufacturer's name, trademark, logo, or symbol; revised two material designation subsections involving standard references for marking nameplates and bodies; updated Tables 1 and 2 involving examples of common symbols for metallic/non-metallic materials; updated terminology; included supplemental material designations (e.g., Bismuth, Bismuth-Selenium, and Silicon) for certain non-ferrous flanges, flanged fittings, and flanged unions; updated Annex B to include many revised and new examples; updated and revised Annex C references; and other revisions to provide clarification as warranted. It was also agreed for the next revision to consider markings for MSS SP-44 flanges and ASME B16.36 orifice flanges. This 2018 revised American National Standard edition was ANSI-approved after being substantively revised, reformatted, and approved by MSS, then submitted unpublished to the ANSI balloting and approval process.

This Page Intentionally Left Blank

Manufacturers Standardization Society of the Valve and Fittings Industry

TABLE OF CONTENTS

SECT	TON GENERAL RULES	
1	SCOPE	1
2	GENERAL MARKING REQUIREMENTS	1
3	MANUFACTURER'S NAME OR TRADEMARK	2
4	RATING DESIGNATION	2
5	MATERIAL DESIGNATION	3
6	HEAT NUMBER	4
7	VALVE TRIM IDENTIFICATION	4
8	SIZE DESIGNATION	_
9	IDENTIFICATION OF THREADED ENDS	5
10	RING-JOINT FACING IDENTIFICATION	6
11	PERMISSIBLE OMISSION OF MARKINGS	6
	SPECIFIC RULES	
12	MARKING REQUIREMENTS FOR FLANGES, FLANGED FITTINGS, AND FLANGED UNIONS	<i>6</i>
13	MARKING REQUIREMENTS FOR THREADED FITTINGS AND UNIONS	7
14	MARKING REQUIREMENTS FOR WELDING AND SOLDER-JOINT FITTINGS	
1.5	AND UNIONS	
15	MARKING REQUIREMENTS FOR NON-FERROUS VALVES	
16	MARKING REQUIREMENTS FOR GRAY IRON VALVES	
17	MARKING REQUIREMENTS FOR DUCTILE IRON VALVES	
18	MARKING REQUIREMENTS FOR STEEL VALVES	1 1
TABL	Æ	
A1	Examples of Common Symbols for Metallic Materials	13
	Examples of Common Symbols for Non-Metallic Materials	
	Size Identification and Equivalency: NPS and DN	
A4	Examples of Thread Type Symbols	14
A5	ASME B16.1 Rating Designations	14
ANNE	$\mathbf{E}\mathbf{X}$	
A	Reference Tables	13
В	Marking Requirement Examples	
C	Performance Standards and Applicable Dates	2.2

STANDARD MARKING SYSTEM FOR VALVES, FITTINGS, FLANGES, AND UNIONS

1. **SCOPE**

- 1.1 This standard marking system applies to the marking of new valves, fittings, flanges, and unions used in piping connections that include (but are not limited to) flanged, soldered, brazed, threaded, or welded joints.
- 1.2 The markings specified within this Standard Practice serve to identify the manufacturer, the rating designation, materials of construction, and special service limitations imposed by the manufacturer. They are used for product identification and to assist in proper application.
- 1.3 Marking for remanufactured and refurbished valves, fittings, flanges, and unions is outside the scope of this Standard Practice.

2. **GENERAL MARKING REQUIREMNTS**

- 2.1 Each product, of a size and shape permitting legible marking, shall be marked in accordance with the provisions of this Standard Practice.
- 2.2 Markings shall be applied to the body of valves, flanges, fittings, and union components, or on an identification plate. For quarter-turn valves, markings shall be applied to the body, identification plate, or handle. Markings on covered quarter-turn valve handles may not be integral with the base handle material.
- 2.3 Markings shall consist of numerals, letters, or symbols that are cast, forged, stamped, electro-etched, vibro-etched, laser-etched, or otherwise made integral with the product, or as markings on an identification plate attached to the product, or both. Where stamping is used on pressure containing walls, low stress stamps which produce a round bottom impression shall be used; such low stress stamps are not required on flanged edges or on raised pads provided for marking purposes.
- 2.4 Markings indicating conformance with recognized documents, such as the ASME Boiler and Pressure Vessel Codes (BPVC), or applicable API, FM, and UL conformance, testing, and/or certification requirements, may be applied only by authorized, licensed, or approved manufacturers.

Such markings shall be applied only to products fully conforming to the applicable qualification, conformance, and/or certification requirements and may be shown on the body or an attached plate, at the option of the manufacturer.

- 2.5 Manufacturers should apply markings indicating conformance with codes and standards such as API, ASME, ASTM, AWWA, and MSS, on products that fully conform to the applicable codes or standards. Partial compliance markings may apply in specific cases, as allowed for by the code or standard. Certain codes and standards specify mandatory product conformance markings and methods. Such markings shall be shown on the body, on an attached plate, or as otherwise specified.
- 2.6 International and Federal commerce laws, Codes, or contracts may require marking of finished products with country of origin. When required, the markings shall be conspicuous and positioned to prevent concealment during inspection, installation, or use.
- 2.7 Flow or pressure indication shall be marked on unidirectional valves. Commonly used markings include arrows or the words "inlet" or "outlet" or "high pressure side" marked at an appropriate end.
- 2.8 Nothing in this Standard Practice shall be construed as prohibiting the use of additional markings such as catalog reference numbers, pattern numbers, pattern numbers, dates, customer specification numbers, etc.