Drain and Bypass Connections

Standard Practice Developed and Approved by the Manufacturers Standardization Society of the Valve and Fittings Industry, Inc. 127 Park Street, NE Vienna, Virginia 22180-4602 Phone: (703) 281-6613 Fax: (703) 281-6671 E-mail: standards@msshq.org



www.msshq.org

This is a preview. Click here to purchase the full publication.

This MSS Standard Practice was developed under the consensus of the MSS Technical Committee 106, *Cast Iron Valves*, and the MSS Coordinating Committee. The content of this Standard Practice is the resulting efforts of knowledgeable and experienced industry volunteers to provide an effective, clear, and non-exclusive standard that will benefit the industry as a whole. This MSS Standard Practice describes minimal requirements and is intended as a basis for common practice by the manufacturer, the user, and the industry at large. It is the responsibility of the user of this Standard Practice to establish appropriate safety and health practices and determine the applicability of regulatory requirements prior to use. The existence of an MSS Standard Practice. Mandatory conformance to this Standard Practice is established only by reference in other documents such as a code, specification, sales contract, or public law, as applicable. MSS has no power, nor does it undertake, to enforce or certify compliance with this document. Any certification or other statement of compliance with the requirements of this Standard Practice shall not be attributable to MSS and is solely the responsibility of the certifier or maker of the statement.

"Unless indicated otherwise within this MSS Standard Practice, other standards documents referenced to herein are identified by the date of issue that was applicable to this Standard Practice at the date of approval of this MSS Standard Practice (see Annex A). This Standard Practice shall remain silent on the validity of those other standards of prior or subsequent dates of issue even though applicable provisions may not have changed."

By publication of this Standard Practice, no position is taken with respect to the validity of any potential claim(s) or of any patent rights in connection therewith. MSS shall not be held responsible for identifying any patent rights. Users are expressly advised that determination of patent rights and the risk of infringement of such rights are entirely their responsibility.

For all MSS Standard Practices, the term "shall" means "must" and "shall not" means "must not".

In this Standard Practice, all text, notes, annexes, tables, figures, and references are construed to be "normative" and essential to understand the standard's message. All appendices, footnotes, or other information denoted as "supplemental", that may be included within this Standard Practice, DO NOT include mandatory or normative requirements.

The U.S. customary units and SI (metric) units in this Standard Practice are regarded separately as the standard and may not be technically equivalent; each should be used independently of the other. Combining or converting values between the two systems may result in non-conformance with this Standard Practice. U.S. customary units was the original system in this Standard Practice and should be taken into account in cases of conflict or incongruity.

This Standard Practice has been substantively revised from the previous 2003 (R2008) edition. It is suggested that if the user is interested in knowing what changes have been made, that a direct page by page comparison should be made of this document and that of the previous edition.

Non-toleranced dimensions in the Standard Practice are nominal unless otherwise specified.

Excerpts of this Standard Practice may be quoted with written permission. Credit lines should read 'Extracted from MSS SP-45-2020 with permission of the publisher, Manufacturers Standardization Society of the Valve and Fittings Industry'. Reproduction and/or electronic transmission or dissemination is prohibited under copyright convention unless written permission is granted by the Manufacturers Standardization Society of the Valve and Fittings Industry Inc. All rights reserved.

Originally Approved: July 1953 Originally Published: 1953 Current Edition Approved: May 2019(January 2020) Current Edition Published: February 2020

MSS is a registered trademark of Manufacturers Standardization Society of the Valve and Fittings Industry, Inc.

Copyright ©, 2020 by Manufacturers Standardization Society of the Valve and Fittings Industry, Inc. Printed in U.S.A.

This is a preview. Click here to purchase the full publication.

FOREWORD

The original 1953 edition of MSS SP-45-1953, *Bypass and Drain Connection Standard*, was a combination of two former MSS Standard Practices: MSS SP-5-1944, *By-Pass Size Standard*, and MSS SP-28-1943, *Drain Tapping Standard*. As the subject matter of these two Standard Practices was so closely related, they were combined as a convenience to the user.

MSS SP-5 was originally adopted in 1924 and applied to steel gate valves only. Bosses on steel castings of that period presented a more complex problem than castings of other metals and the diversification of requests in regard to size, location, and number of bosses on the part of users prompted the MSS to initiate a standardization program on the subject. The original Standard Practice established the number of bosses, minimum O.D. of a boss, and the pipe thread size for steel gate valves in sizes 3 to 24 inch inclusive. The bosses were intended to be used for both drain and bypass connections.

In 1937 a new edition of SP-5 was adopted. This edition was greatly expanded over the original and included both cast iron and steel valves in the gate, globe and angle patterns. The subject matter was confined to by-passes only and standard locations were established for the bypass on each type of valve. Two sets of bypass sizes were established; one for the purpose of warming up main lines before opening the main valve and one for the purpose of balancing the pressure on both sides of the main valve to facilitate its operation. The edition has been reaffirmed periodically up to the promulgation of the new MSS SP-45.

MSS SP-28 was originally adopted in 1937 and was also prompted by the variety of user requests for connections on valves and fittings at odd locations and varying sizes, with and without bosses. MSS SP-28 established standard drain sizes for each size valve and fitting, standard maximum sizes for unbossed tapping's, and standard locations with standard symbols to designate the location. MSS SP-28 was revised in 1945 at which time a standard method of designating openings of reducing fittings was added. This Standard Practice was also periodically reaffirmed.

The 1953 edition of MSS SP-45 combined these two Standard Practices so that the user has all information pertaining to drain and bypass connections in a single document. In this edition the newer methods of making attachments, such as butt welding were recognized.

The 1971 edition expanded the coverage of the document by including coverage of ball valves. In preparing this edition, the entire Standard Practice was reviewed and up-dated to keep pace with the expanding technology.

The 1976 edition expanded the coverage of the bypass sizes to include valves through NPS 48 and the document was metricized.

The 1982 edition expanded the coverage of the document to include plug valves and included a minor change in title to "*By-Pass and Drain Connection Standard*".

The 1987 edition was a reaffirmation of the 1982 edition with no substantive change.

The 1992 edition changed the title to "Bypass and Drain Connections", removed metric units, and made several editorial changes.

The 1998 edition added metric units and made several editorial and format changes.

The 2003 edition was issued with only editorial changes.

The 2008 edition was a reaffirmation of the 2003 edition with one editorial correction in Annex A.

This 2020 edition revised the title to "*Drain and Bypass Connections*", added additional drain sizes, revised Sections 1 through 6, revised Table 1, Table 2 (including Notes), Table 3, and Table 4, updated Figures 1 and 2 (including Notes), updated Annex A references, in addition to other editorial, clarifying, and format related changes.

This is a preview. Click here to purchase the full publication.

TABLE OF CONTENTS

SECTION

1	SCOPE	1
2	STANDARD SYMBOLS, LOCATIONS, AND DEFINITIONS	1
3	STANDARD DRAIN SIZES	1
4	STANDARD BYPASS SIZES	2
5	BYPASS LOCATIONS	3
6	DRAIN AND BYPASS CONNECTION DIMENSIONS	4
7	BOSSES	5
8	REDUCING FITTINGS	6

TABLE

1	Standard Drain Sizes	.1
2	Bypass Sizes	2
3	Connection Dimensions	.4

FIGURE

1	Minimum Pipe Thread Length	4
	Welding Socket Dimensions	
3	Butt Welds	5
4	Boss Diameters	5
5	Method of Designating Location of Opening for Drains and Bypasses	7
6	Method of Designating Location of Opening for Drains	8

ANNEX

A	Referenced Standards and Applicable Dates	9	1
---	---	---	---