Road Vehicles - 60 V and 600 V Single Core (ISO/Metric) Cables - Dimensions, Test Methods and Requirements

SAE/USCAR23-1 July 2017

This is a preview. Click here to purchase the full publication.

ISBN: 978-0-7680-8443-6



SAE/USCAR-23 REVISION 1

Issued Stabilized 2002-09 2017-07

ROAD VEHICLES - 60 V AND 600 V SINGLE CORE (ISO/METRIC) CABLES - DIMENSIONS, TEST METHODS AND REQUIREMENTS

RATIONALE

The wire sizes called out are no longer being specified in new designs. Cable per ISO 19642-3 are now the preferred specification for automotive primary copper cable used in the U.S.

STABILIZED NOTICE

This document has been declared "Stabilized" by USCAR EWCAP and will no longer be subjected to periodic reviews for currency. Users are responsible for verifying references and continued suitability of technical requirements. Newer technology may exist.

The research data, analysis, conclusion, opinions and other contents of this document are solely the product of the authors. Neither the SAE International (SAE) nor the United States Council for Automotive Research (USCAR) certifies the compliance of any products with the requirements of nor makes any representations as to the accuracy of the contents of this document nor to its applicability for purpose. It is the sole responsibility of the user of this document to determine whether or not it is applicable for their purposes.

Copyright © 2017 USCAR

Printed in U.S.A.

SUMMARY OF CONTENTS

1.	SCOPE	4
2.	NORMATIVE REFERENCES	4
3.	TERMS AND DEFINITIONS	4
3.1	60 Volt (V) Cable	4
3.2	600 Volt (V) Cable	
3.3	Cable Family	5
3.4	Nominal (Value)	5
4.	GENERAL	5
4.1	Cable Types	5
4.2	Caution	
4.3	Conductors	6
4.3.	1 Conductor Specifications	6
4.3.	2 Conductor Stranding	6
4.3.	3 Conductor Dimensions	7
4.4	Tests	8
4.5	General Test Conditions	8
4.6	Ovens	
4.7	Testing Representative Conductor Sizes	9
5.	DIMENSIONS	9
5.1	Outside Cable Diameter	
5.1.	1 Test Sample	9
5.1.	rr	9
5.1.	3 Procedure	9