

UL 60079-2

STANDARD FOR SAFETY

Explosive Atmospheres – Part 2: Equipment Protection by Pressurized Enclosure "p"



UL Standard for Safety for Explosive atmospheres – Part 2: Equipment protection by pressurized enclosure "p", UL 60079-2

Sixth Edition, Dated June 2, 2017

Summary of Topics

This revision of ANSI/UL 60079-2 dated September 15, 2021 is being issued to update the title page to reflect the reaffirmation of its ANSI approval. No changes in requirements have been made.

UL 60079-2 is an adoption of IEC 60079-2, Explosive Atmospheres – Part 2: Equipment Protection by Pressurized Enclosure "p" (Edition 6, issued by IEC July, 2014 including corrigendum 1:2015). Please note that the national difference document incorporates all of the U.S. national differences for UL 60079-2.

Text that has been changed in any manner or impacted by UL's electronic publishing system is marked with a vertical line in the margin.

The requirements are substantially in accordance with Proposal(s) on this subject dated June 25, 2021.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form by any means, electronic, mechanical photocopying, recording, or otherwise without prior permission of UL.

UL provides this Standard "as is" without warranty of any kind, either expressed or implied, including but not limited to, the implied warranties of merchantability or fitness for any purpose.

In no event will UL be liable for any special, incidental, consequential, indirect or similar damages, including loss of profits, lost savings, loss of data, or any other damages arising out of the use of or the inability to use this Standard, even if UL or an authorized UL representative has been advised of the possibility of such damage. In no event shall UL's liability for any damage ever exceed the price paid for this Standard, regardless of the form of the claim.

Users of the electronic versions of UL's Standards for Safety agree to defend, indemnify, and hold UL harmless from and against any loss, expense, liability, damage, claim, or judgment (including reasonable attorney's fees) resulting from any error or deviation introduced while purchaser is storing an electronic Standard on the purchaser's computer system.

No Text on This Page

JUNE 2, 2017

(Title Page Reprinted: September 15, 2021)



1

UL 60079-2

Standard for Explosive atmospheres – Part 2: Equipment protection by pressurized enclosure "p"

First Edition – Not Printed Second Edition – Not Printed Third Edition – Not Printed Fourth Edition – Not Printed Fifth Edition – August, 2010

Sixth Edition

June 2, 2017

This ANSI/UL Standard for Safety consists of the Sixth Edition including revisions through September 15, 2021.

The most recent designation of ANSI/UL 60079-2 as a Reaffirmed American National Standard (ANS) occurred on September 15, 2021. ANSI approval for a standard does not include the Cover Page, Transmittal Pages, Title Page, or Preface. The National Difference Page and IEC Foreword are also excluded from the ANSI approval of IEC-based standards.

Comments or proposals for revisions on any part of the Standard may be submitted to UL at any time. Proposals should be submitted via a Proposal Request in UL's On-Line Collaborative Standards Development System (CSDS) at https://csds.ul.com.

UL's Standards for Safety are copyrighted by UL. Neither a printed nor electronic copy of a Standard should be altered in any way. All of UL's Standards and all copyrights, ownerships, and rights regarding those Standards shall remain the sole and exclusive property of UL.

COPYRIGHT © 2021 UNDERWRITERS LABORATORIES INC.

This is a preview. Click here to purchase the full publication.

No Text on This Page

CONTENTS

Preface	eface (UL)		
Nationa	al Differences	11	
FOREV	VORD	13	
INTROI	DUCTION	23	
		0	
1	Scope		
	1DV Modification of Clause 1 to replace with the following:		
2	Normative references		
	2DV Modification of Clause 2 references to replace with the following:		
3	Terms and definitions		
4	Protection levels		
5	Constructional requirements for pressurized enclosures		
	5.1 Enclosure	31	
	5.2 Materials	31	
	5.3 Doors and covers	31	
	5.4 Mechanical strength		
	5.4DV.1 Modification of Clause 5.4, second paragraph to replace with the following	32	
	5.5 Group I and Group II Apertures, partitions, compartments and internal components	33	
	5.5.2DV Modification of Clause 5.5.2 to replace with the following:	33	
	5.6 Apertures for Static Pressurization	34	
	5.7 Insulating materials for Group I equipment		
	5.8 Sealing		
	5.9 Spark and particle barriers		
	5.9DV.1 Modification of Clause 5.9, fifth paragraph to replace with the following		
	5.10 Cells and batteries		
6	Temperature limits		
Ū	6.1 General		
	6.2 For Level of Protection "pxb" or Level of Protection "pyb"		
	6.2DV Modification of Clause 6.2 to replace with the following:		
	6.3 For Level of Protection "pzc"		
7	Safety provisions and safety devices (except for static pressurization)		
,	7.1 Suitability of safety devices for hazardous area		
	7.1 Suitability of safety devices for nazardous area		
	7.1DV Modification of Clause 7.1 to replace with the following.		
	7.2 Integrity of safety devices		
	7.3 Provider of safety devices 7.3DV Modification of Clause 7.3, to replace with the following:		
	, , , , , , , , , , , , , , , , , , ,		
	7.4 Pressurization System evaluated as associated equipment		
	7.5 Sequence diagram for Level of Protection "pxb"		
	7.6 Ratings for safety devices		
	7.7 Group I and Group II Purging automated for Level of Protection "pxb"		
	7.8 Group I or Group II – Purging criteria		
	7.9 Group III – Cleaning		
	7.10 Requirements when a minimum flow rate required		
	7.11 Safety devices to detect minimum overpressure		
	7.11DV.1 Modification of Clause 7.11, first paragraph (item 9 of d) to delete text, it does no		
	apply:		
	7.12 Value of minimum overpressure		
	7.13 Pressurizing multiple enclosures		
	7.14 Safety devices on doors and covers		
	7.15 Equipment that may remain energized	41	

	7.16 Equipment permitted within Level of Protection "pyb"	42
8	Safety provisions and safety devices for static pressurization	
	8.1 Suitability of safety devices for hazardous area	42
	8.2 Protective gas	
	8.3 Internal sources of release	
	8.4 Group I and Group II Filling procedure	
	8.5 Group III Filling Procedure	
	8.6 Safety devices	
	8.7 Equipment that may remain energized	
	8.8 Overpressure	
9	Supply of protective gas	
	9.1 Backup supply	
	9.2 Independent supplies	
	9.3 Type of gas	
	9.4 Temperature	
10	Pressurized equipment with an internal source of release	
11	Release conditions	
	11.1 No release	
	11.1.2DV.1 Modification of Clause 11.1.1, second paragraph to replace with the following: .	
	11.2 Limited release of a gas or vapour	
	11.3 Limited release of a liquid	
12	Design requirements for the containment system	
	12.1 General design requirements	
	12.2 Infallible containment system	
	12.3 Containment system with a limited release	
	12.3DV.1 Modification of Clause 12.3, fourth paragraph to replace with the following:	
13	Protective gas and pressurizing techniques when there is an internal source of release	
	13.1 General	
	13.2 Pressurization with leakage compensation	
	13.3 Pressurization with dilution	
14	Ignition-capable equipment	
15	Internal hot surfaces	
16	Type verification and tests	
	16.1 Determining the maximum overpressure rating	
	16.2 Maximum overpressure test	
	16.3 Leakage test	
	16.4 Purging test for pressurized enclosures with no internal source of release and filling	
	procedure test for static pressurization	49
	16.5 Purging and dilution tests for a pressurized enclosure with an internal source of	
	release	
	16.6 Verification of minimum overpressure	52
	16.7 Tests for an infallible containment system	53
	16.8 Overpressure test for a containment system with a limited release	
17	Routine tests	53
	17.1 Functional test	
	17.2 Leakage test	53
	17.3 Tests for an infallible containment system	
	17.4 Test for a containment system with a limited release	54
18	Marking	54
	18.1 General	
	18.2 Identifying as pressurized	
	18.3 Supplementary marking	
	18.3DV.1 Modification of Clause 18.3, item a) to include permissible substitute marking for	
	level of protection marking for Group III with the following:	
	18.4 Internal source of release	55
	18.5 Static pressurization	55

	18.6 Pressurization systems	
	18.6DV.1 Modification of Clause 18.6, NOTES to replace with the following:	
	18.7 Warnings required in other clauses	
	18.8 Overpressure limited by user	
	18.9 Inert gas	
19	Instructions	57
Annex A	(normative) Purging and dilution tests	
A.1	General	58
A.2	Criteria for compliance where the protective gas is air	58
A.3	Criteria for compliance where the protective gas is inert	58
Annex B	(informative) Examples of functional sequence diagram	
Annex C	(informative) Examples of the changes in pressure in ducts and enclosures	
Annex D	(informative) Information to be provided to the user	
D.1	General	
D.2	Ducting of protective gas	
	D.2.1 Location of inlet	
	D.2.2 Ducting between pressurized enclosure and inlet	
	D.2.3 Outlets for protective gas	
	D.2.4 Additional purge time to account for ducting	
	D.2.5 Temperature of protective gas at the inlet	
D.3	Power for protective gas supply	
D.4	Static pressurization	
D.5	Enclosures with a containment system	
D.6	Enclosure maximum overpressure	70
Annex E	(normative) Classification of the type of release within enclosures	
E.1	General	71
E.2	No normal release, no abnormal release	71
E.3	No normal release, limited abnormal release	
E.4	Limited normal release	71
Annex F	(informative) Examples for the use of the dilution area concept	
	(normative) Internal Cells and Batteries for Level of Protection "pxb" and Protection "pyb"	d Level of
G.1	General Requirements	75
	G.1.1 General	
	G.1.2 Accepted Electrochemical Systems	75
	G.1.3 Secondary cells and secondary batteries	
	G.1.4 Mechanical Protection	75
G.2	Electrical Protection by energy limiting circuits.	75
	G.2.1 Assessing as energy limited	
	G.2.2 Protective Components	76

	following:	76
	G.2.3 Preventing excessive gas pressure	
G.3	Additional requirements for Primary batteries	77
	G.3.1 Prevention of reverse charging	77
	G.3.2 Prevention of accidental charging of primary batteries	78
G.4	Additional requirements for secondary batteries	78
	G.4.1 Charging of secondary batteries inside the pressurized housing	78
G.5	Specific requirements for Inherently Safe (IhS) cells and batteries	79
	Annex G.5DV.1 Modification of Clause G.5, first paragraph to replace with the following	:79
	Annex G.5.2 Modification of Clause G.5, third paragraph to replace with the following:	
G.6	Equipment located inside a pressurized enclosure connected to a battery which is also inside the pressurized enclosure and not disconnected in the event of loss of pressurization.	tion 79
	G.6.1 General	
	G.6.2 Circuit Isolation	
	G.6.3 Intrinsically safe battery or inherently safe battery used with "Ex" equipment	
	G.6.4 Intrinsically Safe or Inherently Safe battery with non-"Ex" equipment	80
G.7	Supplementary marking and constructional requirements for pressurized enclosures containing one or more cells or batteries	
	G.7.1 General	
	G.7.2 Battery removal warning	
	G.7.3 Batteries requiring routine maintenance	
G.8	Type tests	
	G.8.1 Voltage	82
	G.8.2 Short circuit test for an Inherently Safe Cell or Battery	
	G.8.3 Full load test for other than Inherently safe batteries	82
	(normative) Internal Cells and Batteries for Level of Protection "pzc"	
H.1	General Requirements	
	H.1.1 General	
	H.1.2 Accepted Electrochemical Systems	
	H.1.3 Secondary cells and secondary batteries	
	H.1.4 Mechanical Protection	
H.2	Equipment located inside a pressurized enclosure connected to a battery which is also I inside the pressurized enclosure and is not disconnected when power is removed from t	he
	enclosure	
	Annex H.2DV Modification of Clause H.2 to replace with the following:	
H.3	Supplementary marking and constructional requirements for pressurized enclosures connected one or more cells or batteries.	84
	H.3.1 General	
	H.3.2 Battery removal warning	
	H.3.3 Batteries requiring routine maintenance	84

Bibliography