

UL 2560

STANDARD FOR SAFETY

Emergency Call Systems for Assisted Living and Independent Living Facilities



NOVEMBER 8, 2018 – UL 2560 tr1

UL Standard for Safety for Emergency Call Systems for Assisted Living and Independent Living Facilities, UL 2560

First Edition, Dated September 13, 2011

Summary of Topics

This revision of ANSI/UL 2560 was issued to incorporate the following changes:

Addition of alternate standard as option to UL 60950

The new/revised requirements are substantially in accordance with Proposal(s) on this subject dated September 28, 2018.

Text that has been changed in any manner or impacted by UL's electronic publishing system is marked with a vertical line in the margin.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form by any means, electronic, mechanical photocopying, recording, or otherwise without prior permission of UL.

UL provides this Standard "as is" without warranty of any kind, either expressed or implied, including but not limited to, the implied warranties of merchantability or fitness for any purpose.

In no event will UL be liable for any special, incidental, consequential, indirect or similar damages, including loss of profits, lost savings, loss of data, or any other damages arising out of the use of or the inability to use this Standard, even if UL or an authorized UL representative has been advised of the possibility of such damage. In no event shall UL's liability for any damage ever exceed the price paid for this Standard, regardless of the form of the claim.

Users of the electronic versions of UL's Standards for Safety agree to defend, indemnify, and hold UL harmless from and against any loss, expense, liability, damage, claim, or judgment (including reasonable attorney's fees) resulting from any error or deviation introduced while purchaser is storing an electronic Standard on the purchaser's computer system.

No Text on This Page

This is a preview. Click here to purchase the full publication.

SEPTEMBER 13, 2011

(Title Page Reprinted: November 8, 2018)



1

UL 2560

Standard for Emergency Call Systems for Assisted Living and Independent Living Facilities

First Edition

September 13, 2011

This ANSI/UL Standard for Safety consists of the First Edition including revisions through November 8, 2018.

The most recent designation of ANSI/UL 2560 as an American National Standard (ANSI) occurred on November 8, 2018. ANSI approval for a standard does not include the Cover Page, Transmittal Pages, and Title Page.

Comments or proposals for revisions on any part of the Standard may be submitted to UL at any time. Proposals should be submitted via a Proposal Request in UL's On-Line Collaborative Standards Development System (CSDS) at https://csds.ul.com.

UL's Standards for Safety are copyrighted by UL. Neither a printed nor electronic copy of a Standard should be altered in any way. All of UL's Standards and all copyrights, ownerships, and rights regarding those Standards shall remain the sole and exclusive property of UL.

COPYRIGHT © 2018 UNDERWRITERS LABORATORIES INC.

No Text on This Page

CONTENTS

INT	RO	וחו	IC.	ΓIΩ	N
	-			-	41

	1 Scope	
	2 General	
	2.1 System configuration	
	2.2 Components	8
	2.3 Units of measurement	8
	2.4 Undated references	8
	2.5 Maximum voltage and power	8
	3 Glossary	9
~	ONSTRUCTION	
CC	SNSTRUCTION	
	4 General	
	5 Enclosures	
	5.1 General	
	5.2 Cast metal	
	5.3 Sheet metal	
	5.4 Nonmetallic	
	5.5 Ventilating openings	
	5.6 Covers	16
	5.7 Observation opening covers	
	5.8 General enclosure openings – non-resident accessible equipment	
	5.9 Enclosure top openings – non-resident accessible equipment	
	5.10 Enclosure side openings – non-resident accessible equipment	
	5.11 Enclosure bottom openings – non-resident accessible equipment	
	6 Electric Shock	
	7 Corrosion Protection	
	8 Field Wiring System Connections	
	8.1 General	18G
	8.2 Terminals	
	8.3 Leads	
	8.4 Interconnecting wiring	
	8.5 Equipment grounding connection	
	8.6 Supply connections	
	8.7 Grounded supply conductor connection	
	8.8 Compartments	
	8.9 Strain relief	
	9 Internal Wiring	
	9.1 General	
	9.2 Wireways	
	9.3 Splices	
	9.4 Barriers	
	9.5 Bushings	
	10 Bonding for Grounding	
	11 Components	
	11.1 Printed-wiring boards	
	11.2 Coil windings	
	11.3 Switches	
	11.4 Light sources	
	The Light Sources	

	11.5 Protective devices	27
	11.6 Connectors and receptacles	27
	11.7 Pillow speakers/call cords	27
	11.8 Transformers	
	11.9 Current-carrying parts	
	11.10 Insulating material	
	11.11 Mounting of parts	
	11.12 Operating mechanisms	
10	Secondary Power Supply	
12	12.1 General	
	12.2 Power supply supervision test	
	12.3 Battery charging test	
	12.4 Battery discharge test	
	Storage Batteries	
	Spacings	
15	Testing, Servicing, and Maintenance Protection	34
PERFO	RMANCE	
16	General	34
	Normal Operation Test	
18	Electrical Supervision	38
	18.1 General	
	18.2 All centralized systems	
19	Voltage and Current Measurements	
	19.1 Input circuit	
	19.2 Output circuit	
	19.3 Volt-ampere capacity – low-voltage power-limited circuits	
20	Overvoltage and Undervoltage Operation Test	
20		
	20.1 Overvoltage operation	
0.1	20.2 Undervoltage operation	
	Jarring Test	
	Temperature Test	
23	Overload Test	
	23.1 Signaling unit	
	23.2 Separately energized circuits	
	Endurance Test	
	Variable Ambient Temperature Test	
	Humidity Test	
27	Electric Shock Current Test	50
28	Leakage Current Test	54
29	Transient Test	56
	29.1 General	56
	29.2 Supply line transients – high-voltage units	
	29.3 Internally induced transients – all units	
30	Dielectric Voltage-Withstand Test	
	Static Discharge Test	
	Drop Test	
	Component Failure Test	
	Abnormal Tests	
54		
	34.1 Abnormal operation test	
	34.2 Burnout test	
	34.3 Circuit isolation – supplementary equipment	

	35 Tests for Special Terminal Assemblies	61
	35.1 General	61
	35.2 Mechanical secureness test	6
	35.3 Flexing test	61
	35.4 Millivolt drop test	62
	35.5 Terminal temperature test	62
	36 Polymeric Materials Test	62
	36.1 General	62
	36.2 Temperature test	62
	36.3 3/4-inch flame test	63
	36.4 5-inch flame test	64
	37 Strain Relief Test	65
	37.1 Power supply cord	65
	37.2 Field wiring leads	65
	38 Water Spray and Submersion Tests	66
	38.1 Water spray test	
	38.2 Submersion test	68
	39 Impact Test	68
	40 Wireless Devices	
	40.1 General	68
	40.2 Primary batteries	
	40.3 Low-power radio-frequency signaling	
	40.4 Frequency selectivity	
	40.5 Clash	
	40.6 Clash error	
	40.7 Error (falsing) rate	
	40.8 Throughput rate	
	40.9 Transmitter stability tests	
	40.10 Transmitter accelerated aging test	
	40.11 Reference level determination	
	41 Primary Batteries Test	
	41.1 Life test	
	41.2 Battery trouble voltage determination	
	41.3 Battery replacement test	80
	41.4 Butt-type connection pressure test	
	41A Outdoor Use	
	41A.1 General	
	41A.2 Corrosion tests	
	41A.3 Dust test	
	41A.4 Water spray test	
	41A.5 Gasket testing	
	41A.6 Polymeric materials – outdoor use tests	
	41A.7 Outdoor conditioning test	
	41B Ignition Test Through Bottom-Panel Openings	
MAN	IUFACTURING AND PRODUCTION TESTS	
	42 Production-Line Dielectric Voltage-Withstand Test	82F
	43 Production-Line Grounding Continuity Test	820
МДР	KINGS	
IVI PA [T		
	44 Coperal	920

	45 Label Design	
	46 Label Colors	86
INS	STRUCTIONS AND INSTALLATION DRAWINGS	
	47 Details	86
PR	OGRAM-CONTROLLED AND SIGNALING EQUIPMENT AND SYSTEMS	
	48 General	88
	49 Program Access and Control	88
ΑP	PENDIX A	
	Standards for Components	Δ1

INTRODUCTION

1 Scope

- 1.1 These requirements cover the individual unit employed to form assisted and independent living emergency call systems (ECS) intended to provide audible and visual signaling between residents and assisted and independent living facility staff. Some examples include call initiation stations, call notification stations, and power supplies.
- 1.2 The units covered by these requirements are intended to be installed in either general or resident areas in accordance with the National Electrical Code, NFPA 70.
- 1.3 These requirements are not intended to cover signaling systems in a hospital or acute/skilled care environment. Requirements for systems of this nature are covered by the Standard for Hospital Signaling and Nurse Call Equipment, UL 1069.

2 General

2.1 System configuration

- 2.1.1 The minimum fundamental configuration shall consist of the following:
 - a) An emergency call-initiation station with a call assurance indicator suitable for permanent installation in each resident living unit. Typical applications will utilize pendants for residents, multiple call initiation stations in each living unit, and additional call initiation stations in common areas within the facility.
 - b) Call notification station(s) that receive calls, one of which must be installed at a fixed location.
- 2.1.2 An ECS employs a dedicated wired, dedicated wireless, or combination of these means for initiation of a resident or staff call, requiring attention.
- 2.1.3 An Emergency Call System has a Secondary (battery backup) Power Supply. The length of backup is specified by the manufacturer.