



UL 651A

STANDARD FOR SAFETY

Schedule 40 and 80 High Density Polyethylene (HDPE) Conduit

UL Standard for Safety for Schedule 40 and 80 High Density Polyethylene (HDPE) Conduit, UL 651A
Fifth Edition, Dated October 26, 2011

Summary of Topics

This revision was issued to incorporate the following changes

1. Correction to explanatory or approximate impact weight value stated in parentheses.

The new requirements are substantially in accordance with Proposal(s) on this subject dated January 27, 2017.

Text that has been changed in any manner or impacted by UL's electronic publishing system is marked with a vertical line in the margin.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form by any means, electronic, mechanical photocopying, recording, or otherwise without prior permission of UL.

UL provides this Standard "as is" without warranty of any kind, either expressed or implied, including but not limited to, the implied warranties of merchantability or fitness for any purpose.

In no event will UL be liable for any special, incidental, consequential, indirect or similar damages, including loss of profits, lost savings, loss of data, or any other damages arising out of the use of or the inability to use this Standard, even if UL or an authorized UL representative has been advised of the possibility of such damage. In no event shall UL's liability for any damage ever exceed the price paid for this Standard, regardless of the form of the claim.

Users of the electronic versions of UL's Standards for Safety agree to defend, indemnify, and hold UL harmless from and against any loss, expense, liability, damage, claim, or judgment (including reasonable attorney's fees) resulting from any error or deviation introduced while purchaser is storing an electronic Standard on the purchaser's computer system.

No Text on This Page

OCTOBER 26, 2011
(Title Page Reprinted: March 10, 2017)



ANSI/UL 651A-2017

1

UL 651A

Schedule 40 and 80 High Density Polyethylene (HDPE) Conduit

Prior to the first edition, the requirements for the products covered by this standard were included in the Standard for Rigid Nonmetallic Conduit, UL 651.

Prior to the fifth edition, the requirements for continuous length HDPE conduit covered by this standard were included in the Standard for Continuous Length HDPE Conduit, UL 651B.

First Edition – May, 1981
Second Edition – August, 1989
Third Edition – August, 1995
Fourth Edition – October, 2000

Fifth Edition

October 26, 2011

This ANSI/UL Standard for Safety consists of the Fifth Edition including revisions through March 10, 2017.

The most recent designation of ANSI/UL 651A as an American National Standard (ANSI) occurred on March 10, 2017. ANSI approval for a standard does not include the Cover Page, Transmittal Pages and Title Page.

The Department of Defense (DoD) has adopted UL 651A on November 30, 1984. The publication of revised pages or a new edition of this Standard will not invalidate the DoD adoption.

Comments or proposals for revisions on any part of the Standard may be submitted to UL at any time. Proposals should be submitted via a Proposal Request in UL's On-Line Collaborative Standards Development System (CSDS) at <https://csds.ul.com>.

UL's Standards for Safety are copyrighted by UL. Neither a printed nor electronic copy of a Standard should be altered in any way. All of UL's Standards and all copyrights, ownerships, and rights regarding those Standards shall remain the sole and exclusive property of UL.

COPYRIGHT © 2017 UNDERWRITERS LABORATORIES INC.