




ANSI/CAN/UL 9540A:2019 JOINT CANADA-UNITED STATES NATIONAL STANDARD

STANDARD FOR SAFETY

Test Method for Evaluating Thermal Runaway Fire Propagation in Battery Energy Storage Systems





SCC FOREWORD

National Standard of Canada

A National Standard of Canada is a standard developed by a Standards Council of Canada (SCC) accredited Standards Development Organization, in compliance with requirements and guidance set out by SCC. More information on National Standards of Canada can be found at www.scc.ca.

SCC is a Crown corporation within the portfolio of Innovation, Science and Economic Development (ISED) Canada. With the goal of enhancing Canada's economic competitiveness and social well-being, SCC leads and facilitates the development and use of national and international standards. SCC also coordinates Canadian participation in standards development, and identifies strategies to advance Canadian standardization efforts.

Accreditation services are provided by SCC to various customers, including product certifiers, testing laboratories, and standards development organizations. A list of SCC programs and accredited bodies is publicly available at www.scc.ca.

UL Standard for Safety for Test Method for Evaluating Thermal Runaway Fire Propagation in Battery Energy Storage Systems, ANSI/CAN/UL 9540A:2019

Fourth Edition, Dated November 12, 2019

Summary of Topics

This Fourth Edition of ANSI/CAN/UL 9450A, Standard for Safety for Test Method for Evaluating Thermal Runaway Fire Propagation in Battery Energy Storage Systems, has been issued to reflect the latest ANSI and SCC approval dates, and to incorporate the proposals dated March 29, 2019 and August 16, 2019.

The requirements are substantially in accordance with Proposal(s) on this subject dated March 29, 2019 and August 16, 2019.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form by any means, electronic, mechanical photocopying, recording, or otherwise without prior permission of UL.

UL provides this Standard "as is" without warranty of any kind, either expressed or implied, including but not limited to, the implied warranties of merchantability or fitness for any purpose.

In no event will UL be liable for any special, incidental, consequential, indirect or similar damages, including loss of profits, lost savings, loss of data, or any other damages arising out of the use of or the inability to use this Standard, even if UL or an authorized UL representative has been advised of the possibility of such damage. In no event shall UL's liability for any damage ever exceed the price paid for this Standard, regardless of the form of the claim.

Users of the electronic versions of UL's Standards for Safety agree to defend, indemnify, and hold UL harmless from and against any loss, expense, liability, damage, claim, or judgment (including reasonable attorney's fees) resulting from any error or deviation introduced while purchaser is storing an electronic Standard on the purchaser's computer system.

No Text on This Page

This is a preview. Click here to purchase the full publication.



NOVEMBER 12, 2019



1

ANSI/CAN/UL 9540A:2019

Standard for Test Method for Evaluating Thermal Runaway Fire Propagation in Battery Energy Storage Systems

First Edition – November, 2017 Second Edition – January, 2018 Third Edition – June, 2018

Fourth Edition

November 12, 2019

This ANSI/CAN/UL Safety Standard consists of the Fourth Edition.

The most recent designation of ANSI/UL 9540A as an American National Standard (ANSI) occurred on November 12, 2019. ANSI approval for a standard does not include the Cover Page, Transmittal Pages, Title Page, Preface or SCC Foreword.

This standard has been designated as a National Standard of Canada (NSC) on November 12, 2019.

© 2019 UNDERWRITERS LABORATORIES INC.

No Text on This Page

CONTENTS

Preface			5
INTRO	DUCTIO	N	
1	Scope.		9
2		Measurement	
3		ive References	
4		γ	
		,	
CONS	TRUCTIO	DN Comments of the comments of	
5			13
	5.1	Cell	
	5.2	Module	13
	5.3	Battery energy storage system unit	
	5.4	Flow Batteries	14
PERFO	ORMANC	E	
6	Genera	I	14
7		/el	
,	7.1	General	
	7.1	Sample	
	7.3	Determination of thermal runaway methodology	
	7.4	Cell vent gas composition test	
	7.5	Off gas composition for flow battery systems	
	7.6	Cell level test report	
	7.7	Performance – cell level test	
	7.8	Performance – flow battery thermal runaway determination tests	
9		Level	
	8.1	Sample	
	8.2	Test method	
	8.3	Module level test report	
	8.4	Performance at module level testing	
	Unit Le	Unit Level	
	9.1	Sample and test configuration	24
	9.2	Test method – Indoor floor mounted BESS units	28
	9.3	Test method – Outdoor ground mounted units	32
	9.4	Test Method – Indoor wall mounted units	32
	9.5	Test Method – Outdoor wall mounted units	33
	9.6	Rooftop and open garage installations	
	9.7	Unit level test report	33
	9.8	Performance at unit level testing	35
10) Install	ation Level	
	10.1	General	
	10.2	Sample	
	10.3	Test method 1 – Effectiveness of sprinklers	
	10.4	Installation level test report – Test method 1 – Effectiveness of sprinklers	
	10.5	Performance – Test method 1 – Effectiveness of sprinklers	
	10.6	Test method 2 – Effectiveness of fire protection plan	
	10.7	Installation level test report – Test method 2 – Effectiveness of fire protection plan	
	10.8	Performance – Test method 2 – Effectiveness of fire protection plan	43