



UL 2459

STANDARD FOR SAFETY

Insulated Multi-Pole Splicing Wire Connectors

UL Standard for Safety for Insulated Multi-Pole Splicing Wire Connectors, UL 2459

First Edition, Dated August 22, 2008

Summary of Topics

This revision of ANSI/UL 2459 includes the following changes in requirements:

Minimum Spacings Table 4

Intermateability of Connectors

Use of Multi-Pole Splicing Wire Connectors as Disconnects in LED Applications

Text that has been changed in any manner or impacted by UL's electronic publishing system is marked with a vertical line in the margin.

The new and revised requirements are substantially in accordance with Proposal(s) on this subject dated May 4, 2018.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form by any means, electronic, mechanical photocopying, recording, or otherwise without prior permission of UL.

UL provides this Standard "as is" without warranty of any kind, either expressed or implied, including but not limited to, the implied warranties of merchantability or fitness for any purpose.

In no event will UL be liable for any special, incidental, consequential, indirect or similar damages, including loss of profits, lost savings, loss of data, or any other damages arising out of the use of or the inability to use this Standard, even if UL or an authorized UL representative has been advised of the possibility of such damage. In no event shall UL's liability for any damage ever exceed the price paid for this Standard, regardless of the form of the claim.

Users of the electronic versions of UL's Standards for Safety agree to defend, indemnify, and hold UL harmless from and against any loss, expense, liability, damage, claim, or judgment (including reasonable attorney's fees) resulting from any error or deviation introduced while purchaser is storing an electronic Standard on the purchaser's computer system.

No Text on This Page



Canadian Standards Association
CSA C22.2 No. 2459-08
First Edition



Underwriters Laboratories Inc.
UL 2459
First Edition

Insulated Multi-Pole Splicing Wire Connectors

August 22, 2008

(Title Page Reprinted: September 20, 2018)



ANSI/UL 2459-2018

This is a preview. [Click here to purchase the full publication.](#)

Commitment for Amendments

This standard is issued jointly by the Canadian Standards Association (operating as “CSA Group”) and Underwriters Laboratories Inc. (UL). Comments or proposals for revisions on any part of the standard may be submitted to CSA Group or UL at anytime. Revisions to this standard will be made only after processing according to the standards development procedures of CSA Group and UL. CSA Group and UL will issue revisions to this standard by means of a new edition or revised or additional pages bearing their date of issue.

ISBN 1-55436-435-3 © 2008 Canadian Standards Association

All rights reserved. No part of this publication may be reproduced in any form whatsoever without the prior permission of the publisher.

This Standard is subject to review within five years from the date of publication, and suggestions for its improvement will be referred to the appropriate committee. To submit a proposal for change, please send the following information to inquires@csagroup.org and include “Proposal for change” in the subject line: Standard designation (number); relevant clause, table, and/or figure number; wording of the proposed change; and rationale for the change.

To purchase CSA Group Standards and related publications, visit CSA Group’s Online Store at shop.csa.ca or call toll-free 1-800-463-6727 or 416-747-4044.

Copyright © 2018 Underwriters Laboratories Inc.

UL’s Standards for Safety are copyrighted by UL. Neither a printed nor electronic copy of a Standard should be altered in any way. All of UL’s Standards and all copyrights, ownerships, and rights regarding those Standards shall remain the sole and exclusive property of UL.

This ANSI/UL Standard for Safety consists of the First edition including revisions through September 20, 2018. The most recent designation of ANSI/UL 2459 as an American National Standard (ANSI) occurred on September 20, 2018. ANSI approval for a standard does not include the Cover Page, Transmittal Pages, Title Page (front and back), or the Preface.

Comments or proposals for revisions on any part of the Standard may be submitted to UL at any time. Proposals should be submitted via a Proposal Request in UL’s On-Line Collaborative Standards Development System (CSDS) at <https://csds.ul.com>.

To purchase UL Standards, visit UL’s Standards Sales Site at <http://www.shopulstandards.com/HowToOrder.aspx> or call toll-free 1-888-853-3503.

CONTENTS

| | |
|--------------------------------------------------------------------|----------|
| Preface | 5 |
| 1 Scope | 6A |
| 2 Reference publications and definitions | 8 |
| 2.1 Reference publications | 8 |
| 2.2 Definitions | 9 |
| 3 Units of measurement | 11 |
| 4 Construction | 11 |
| 4.1 General | 11 |
| 4.2 Materials | 12 |
| 4.3 Accessibility of parts | 14 |
| 4.4 Spacings | 15 |
| 4.5 Mating-type (separable-type) connectors | 16 |
| 4.6 Integral pigtail leads | 16 |
| 5 Test requirements | 16 |
| 5.1 General | 16 |
| 5.2 Grounding contact – Short-time withstand current | 17 |
| 5.3 Latching mechanism | 17 |
| 5.4 Abnormal overload | 18 |
| 5.5 Temperature | 18 |
| 5.6 Dielectric voltage withstand | 18 |
| 5.7 Dielectric withstand – Puncture | 19 |
| 5.8 Mold stress relief | 19 |
| 5.9 Current cycling | 20 |
| 5.10 Mechanical sequence | 21 |
| 5.11 Stress corrosion/moist ammonia (NH ₄) | 21 |
| 5.12 Stress corrosion/mercurous nitrate (HgNO ₃) | 21 |
| 5.13 Spring action | 21 |
| 6 Sampling requirements | 21 |
| 7 Test methods | 22 |
| 7.1 General | 22 |
| 7.2 Grounding contact – Short-time withstand current | 28 |
| 7.3 Latching or locking mechanism | 29 |
| 7.4 Abnormal overload | 29 |
| 7.5 Temperature rise | 30 |
| 7.6 Dielectric voltage withstand | 31 |
| 7.7 Dielectric withstand – Puncture | 31 |
| 7.8 Mold stress relief | 32 |
| 7.9 Current cycling | 32 |
| 7.10 Mechanical sequence | 33 |
| 7.11 Stress corrosion/moist ammonia (NH ₄) | 34 |
| 7.12 Stress corrosion/mercurous nitrate (HgNO ₃) | 35 |
| 7.13 Spring-action sequence | 35 |
| 8 Marking, labelling, and packaging | 36 |
| TABLES | 39 |
| FIGURES | 47 |

Annex A (Informative)

| | |
|-----------------------------------------------------|----|
| A.1 Example of a stability factor calculation | 54 |
|-----------------------------------------------------|----|

Annex B (Informative)

| | |
|-----------------------------------------------------|----|
| B.1 Example of application of Clause 7.10.2.4 | 55 |
|-----------------------------------------------------|----|

Annex C (Informative)

| | |
|--------------------------------------------|----|
| C.1 French translations and markings | 56 |
|--------------------------------------------|----|